

## Han-Yellock side entry M20 white



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 11 12 300 1510                                                                        |
| Specification      | Han-Yellock side entry M20 white                                                      |
| HARTING eCatalogue | <a href="https://b2b.harting.com/11123001510">https://b2b.harting.com/11123001510</a> |

### Identification

|                             |                |
|-----------------------------|----------------|
| Category                    | Hoods/Housings |
| Series of hoods/housings    | Han-Yellock®   |
| Type of hood/housing        | Shell          |
| Description of hood/housing | White          |

### Version

|                      |                                            |
|----------------------|--------------------------------------------|
| Locking type         | Push button                                |
| Size                 | Han-Yellock® 30                            |
| Version              | Side entry                                 |
| Cable entry          | 1x M20                                     |
| Field of application | Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Un-/locking temperature                | -10 ... +85 °C  |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67    |

### Material properties

|                         |                                   |
|-------------------------|-----------------------------------|
| Material (hood/housing) | Aluminium die-cast                |
| Surface (hood/housing)  | Powder-coated                     |
| Colour (hood/housing)   | RAL 1013 (white)                  |
| Material (locking)      | Polyamide (PA)<br>Stainless steel |



Pushing Performance

## Material properties

|                                           |           |
|-------------------------------------------|-----------|
| Material flammability class acc. to UL 94 | V-0       |
| RoHS                                      | compliant |
| ELV status                                | compliant |
| China RoHS                                | e         |
| REACH Annex XVII substances               | No        |
| REACH ANNEX XIV substances                | No        |
| REACH SVHC substances                     | No        |

## Specifications and approvals

|                |                         |
|----------------|-------------------------|
| Specifications | EN 60664-1<br>IEC 61984 |
| Approvals      | DNV GL                  |
| CE             | Yes                     |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 119 g                                    |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |