

Han-Yellock 60 carrier hood button plain



| Part number | 11 12 600 0100 |
|--------------------|--|
| Specification | Han-Yellock 60 carrier hood button plain |
| HARTING eCatalogue | https://b2b.harting.com/11126000100 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|-----------------------------|--------------------------|
| Series of hoods/housings | Han-Yellock [®] |
| Type of hood/housing | Carrier hood |
| Description of hood/housing | Plain push button |

Version

| Locking type | Push button |
|----------------------|--|
| Size | Han-Yellock [®] 60 |
| Field of application | Hoods/housings for industrial applications |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Un-/locking temperature | -10 +85 °C |
| Mating cycles | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |
| | IP67 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-------------------------|--------------------|
| Surface (hood/housing) | Passivated |
| Colour (hood/housing) | Metallic |
| Material (seal) | NBR |
| Material (locking) | Polyamide (PA) |
| | Stainless steel |



Material properties

| Colour (locking) | Melon yellow |
|---|--------------|
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| Specifications | EN 60664-1 IEC 61984 |
|----------------|-------------------------|
| Approvals | DNV GL |
| CE | Yes |

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 248.5 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |