

## Han-Yellock shell top entry M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 11 12 600 1401                                                                        |
| Specification      | Han-Yellock shell top entry M25                                                       |
| HARTING eCatalogue | <a href="https://b2b.harting.com/11126001401">https://b2b.harting.com/11126001401</a> |

### Identification

|                          |                |
|--------------------------|----------------|
| Category                 | Hoods/Housings |
| Series of hoods/housings | Han-Yellock®   |
| Type of hood/housing     | Shell          |

### Version

|                      |                                            |
|----------------------|--------------------------------------------|
| Locking type         | Push button                                |
| Size                 | Han-Yellock® 60                            |
| Version              | Top entry                                  |
| Cable entry          | 1x M25                                     |
| Field of application | Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Un-/locking temperature                | -10 ... +85 °C  |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67    |

### Material properties

|                                           |                       |
|-------------------------------------------|-----------------------|
| Material (hood/housing)                   | Aluminium die-cast    |
| Surface (hood/housing)                    | Powder-coated         |
| Colour (hood/housing)                     | RAL 7021 (black grey) |
| Material flammability class acc. to UL 94 | V-0                   |
| RoHS                                      | compliant             |



Pushing Performance

## Material properties

|                             |           |
|-----------------------------|-----------|
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |

## Specifications and approvals

|                |                         |
|----------------|-------------------------|
| Specifications | EN 60664-1<br>IEC 61984 |
| Approvals      | DNV GL                  |
| CE             | Yes                     |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 158.7 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |