

Han CGM-P-EXi M40 D 22...32mm



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 00 000 7109 |
| Specification | Han CGM-P-EXi M40 D 22...32mm |
| HARTING eCatalogue | https://b2b.harting.com/19000007109 |

Identification

| | |
|--------------------------|---------------------------|
| Category | Accessories |
| Series of hoods/housings | Han [®] CGM-Ex i |
| Type of accessory | Cable gland |

Version

| | |
|----------------------|--------------------------------------|
| Field of application | Intrinsically safe electric circuits |
|----------------------|--------------------------------------|

Technical characteristics

| | |
|--|--|
| Tightening torque | ≤10 Nm (depending on the cable and the seal insert used) |
| Wrench size | 53 |
| Limiting temperature | -40 ... +100 °C |
| Degree of protection acc. to IEC 60529 | IP68 IP69 / IPX9K acc. to ISO 20653 |
| Size | M40 |
| Clamping range | 22 ... 32 mm |
| Width across corners | 58.8 mm |

Material properties

| | |
|---|--|
| Material (seal) | NBR |
| Material (cable glands) | Polyamide (PA) |
| Colour (accessories) | RAL 7032 (pebble grey) RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |



Pushing Performance

Material properties

| | |
|-----------------------------|-----------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 68.8 g |
| Country of origin | Germany |
| European customs tariff number | 39269097 |
| eCl@ss | 27144432 Screwed cable gland (electr.) |