

## Han 6B Ex-HTE-LC-M20 for SL



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 36 006 1440                                                                        |
| Specification      | Han 6B Ex-HTE-LC-M20 for SL                                                           |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19360061440">https://b2b.harting.com/19360061440</a> |

### Identification

|                          |                     |
|--------------------------|---------------------|
| Category                 | Hoods / Housings    |
| Series of hoods/housings | Han <sup>®</sup> Ex |
| Type of hood/housing     | Hood                |

### Version

|                         |                                                              |
|-------------------------|--------------------------------------------------------------|
| Size                    | 6 B                                                          |
| Version                 | Top entry                                                    |
| Number of cable entries | 1                                                            |
| Cable entry             | 1x M20                                                       |
| Locking type            | Single locking lever                                         |
| Field of application    | Connectors for explosion hazardous environments              |
| Details                 | ATTENTION! Only to be used with Han <sup>®</sup> Ex inserts! |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Limiting temperature                   | -20 ... +40 °C                                 |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 With cable gland                          |

### Material properties

|                         |                     |
|-------------------------|---------------------|
| Material (hood/housing) | Zinc die-cast       |
| Surface (hood/housing)  | Powder-coated       |
| Colour (hood/housing)   | RAL 5015 (sky blue) |
| RoHS                    | compliant           |



Pushing Performance  
Since 1945

Material properties

|                                      |               |
|--------------------------------------|---------------|
| ELV status                           | compliant     |
| China RoHS                           | e             |
| REACH Annex XVII substances          | Not contained |
| REACH ANNEX XIV substances           | Not contained |
| REACH SVHC substances                | Not contained |
| California Proposition 65 substances | Yes           |
| California Proposition 65 substances | Lead          |
|                                      | Nickel        |

Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 200 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140128309                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |