

Han 3M-SIS-SL-M20



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 37 003 1150 |
| Specification | Han 3M-SIS-SL-M20 |
| HARTING eCatalogue | https://b2b.harting.com/19370031150 |

Identification

| | |
|--------------------------|-----------------------|
| Category | Hoods / Housings |
| Series of hoods/housings | Han® M |
| Type of hood/housing | Screw mounted housing |

Version

| | |
|-------------------------|---------------------------------------|
| Size | 3 A |
| Number of cable entries | 1 |
| Cable entry | 1x M20 |
| Locking type | Single locking lever |
| Field of application | Hoods/housings for rough environments |
| Pack contents | With seal screw |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP44 |
| | IP65 With seal screw |
| | IP67 With seal screw |

Material properties

| | |
|-------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (locking) | Stainless steel |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|--|
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R1 (HL 1-3) R7 (HL 1-3) |

Specifications and approvals

| | |
|-----------|--------------|
| Approvals | CE DNV GL |
|-----------|--------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 57.67 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140128330 |
| ETIM | EC000437 |
| eCI@ss | 27440202 Shell for industrial connectors |