

## Han 3EMC-HAE-M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 62 003 1645                                                                        |
| Specification      | Han 3EMC-HAE-M25                                                                      |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19620031645">https://b2b.harting.com/19620031645</a> |

### Identification

|                          |                      |
|--------------------------|----------------------|
| Category                 | Hoods / Housings     |
| Series of hoods/housings | Han <sup>®</sup> EMC |
| Type of hood/housing     | Hood                 |

### Version

|                         |                                            |
|-------------------------|--------------------------------------------|
| Size                    | 3 A                                        |
| Version                 | Side entry                                 |
| Number of cable entries | 1                                          |
| Cable entry             | 1x M25                                     |
| Locking type            | Single locking lever                       |
| Field of application    | Hoods/Housings for higher EMC requirements |
| Pack contents           | Please order seal screw separately.        |

### Technical characteristics

|                                        |                                                      |
|----------------------------------------|------------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                      |
| Note on the limiting temperature       | For use as a connector according to IEC 61984.       |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 With seal screw<br>IP67 With seal screw |

### Material properties

|                         |               |
|-------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing)  | Uncoated      |
| Colour (hood/housing)   | Unpainted     |



Pushing Performance  
Since 1945

Material properties

|                                      |               |
|--------------------------------------|---------------|
| RoHS                                 | compliant     |
| ELV status                           | compliant     |
| China RoHS                           | e             |
| REACH Annex XVII substances          | Not contained |
| REACH ANNEX XIV substances           | Not contained |
| REACH SVHC substances                | Not contained |
| California Proposition 65 substances | Yes           |
| California Proposition 65 substances | Lead          |
|                                      | Nickel        |

Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | CE     |
|           | DNV GL |

Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 10                                       |
| Net weight                     | 80.5 g                                   |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140171435                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |