

# Han 24EMC/B-HSE-M40 (HT)



Part number	19 62 824 0528
Specification	Han 24EMC/B-HSE-M40 (HT)
HARTING eCatalogue	https://b2b.harting.com/19628240528

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Hoods / Housings
Series of hoods/housings	Han <sup>®</sup> EMC/B
	Han <sup>®</sup> High Temp
Type of hood/housing	Hood
Туре	High construction

#### Version

Size	24 B
Version	Side entry
Number of cable entries	1
Cable entry	1x M40
Locking type	Double locking lever
Field of application	Hoods/Housings for higher EMC requirements

#### Technical characteristics

Limiting temperature	-40 +125 °C -40 +200 °C With Han® High Temp components
Note on the limiting temperature	For use as a connector according to IEC 61984.
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP66
Type rating acc. to UL 50 / UL 50E	4 12



## Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel

# Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Approvals	CE DNV GL

### Commercial data

Packaging size	1
Net weight	228 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140133105
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors