

FO Contact 230HCS Cab.dm 2,8



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 20 10 230 5211 |
| Specification | FO Contact 230HCS Cab.dm 2,8 |
| HARTING eCatalogue | https://harting.com/20102305211 |

Identification

| | |
|----------------------------|--------------|
| Category | Contacts |
| Series | SC |
| Type of contact | FO contact |
| Description of the contact | for HCS®/PCF |

Version

| | |
|-----------------------|-----------------|
| Manufacturing process | Turned contacts |
|-----------------------|-----------------|

Technical characteristics

| | |
|----------------------|----------------|
| Limiting temperature | -40 ... +85 °C |
|----------------------|----------------|

Material properties

| | |
|-----------------------------|---------------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |

Commercial data

| | |
|-------------------|---------|
| Packaging size | 1 |
| Net weight | 6.7 g |
| Country of origin | Germany |



Pushing Performance
Since 1945

Commercial data

| | |
|--------------------------------|--|
| European customs tariff number | 85367000 |
| GTIN | 5713140133709 |
| ETIM | EC000796 |
| eCl@ss | 27440204 Contact for industrial connectors |