



| PART NUMBER | CABLE O.D. RANGE |
|-------------|-------------------------------|
| S15KS20 | Ø 0.205 - 0.225 [5.21 - 5.72] |
| S15KS23 | Ø 0.235 - 0.255 [5.97 - 6.48] |
| S15KS26 | Ø 0.265 - 0.285 [6.73 - 7.24] |

CUSTOMER DRAWING

- NOTES:**
1. RATED 15 AMP, 24 VOLT DC AT 105° C (CURRENT CARRY ONLY) WHEN USING 14 AWG STRANDED CONDUCTOR CABLE.
 2. USE CABLE LUBE WHEN ASSEMBLING CABLE.
 3. IP68 RATED WHEN MATED TO ST15S JACK.
 4. HANDLE SHIPPED UNASSEMBLED.
 5. THIS PRODUCT IS ROHS COMPLIANT.

| REV | ECO NUMBER | DATE | BY | APVD |
|-----------|------------|---------|-----|------|
| A | 28515 | 7/18/22 | TJK | TJK |
| REVISIONS | | | | |

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES [mm]
 - TWO PLACE DECIMALS ±0.02 [0.5]
 - THREE PLACE DECIMALS ±0.005 [0.13]

DO NOT SCALE DRAWING

| | | | | | | | | | |
|--|-------|------|-----------|--------|---------------------------------|--|-----|--|--|
| THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | | | | | | |
| SIZE | WIDTH | MULT | LBS/M | TEMPER | | | | | |
| FINISH SPEC No. | | | | | MATERIAL SPEC No. | | | | |
| FIRST USED ON | | | SCALE 2:1 | | Switchcraft [®] | | | | |
| DATE DRAWN | BY | CHKD | APVD | | | | | | |
| 5-13-19 | SRC | SRC | TJK | | SHEET 1 OF 1 | | | | |
| NAME | | | | | PART No. | | REV | | |
| 15 AMP SEALED PLUG, RoHS | | | | | S15KS SERIES | | A | | |