
REVISION

RECOMMENDED PCB LAYOUT FOR MEC6-1XX-XX-X-DV-XX


4/13/2011 ECN-152287



-40 POSITION SHOWN (USE FOR 10, 20, 30 & 40 POSITIONS)

DESIGNED & DIMENSIONED IN MILLIMETERS [INCHES]

TABLE 2					
POSITION	"A"	"E"			
-10	5.72[.225]	8.72[.343]			
-20	12.07[.475]	15.07[.593]			
-30	18.42[.725]	21.42[.843]			
-40	24.77[.975]	27.77[1.093]			



-50 POSITION SHOWN

(USE FOR 50, 60 & 70 POSITIONS)

TABLE 1					
POSITION	"A"	"B"	"C"	"E"	
-50	34.29[1.350]	30	19.050[.7500]	37.29[1.468]	
-60	40.64[1.600]	36	22.860[.9000]	43.64[1.718]	
-70	46.99[1.850]	42	26.670[1.0500]	49.99[1.968]	

F:\DWG\MISC\mktg\FOOTPRNT\MEC6-1XX-XX-X-DV-XX-FOOTPRINT.SLDDRW

TOLERANCES ARE: DECIMALS

.X: ±.3 [.01] .XX: ±.10 [.004] .XXX: ±.050 [.0020]

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.



PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com code: 5532 code: 55322

SHEET 1 OF 3

REVISION F

RECOMMENDED STENCIL LAYOUT FOR MEC6-1XX-XX-X-DV-XX

F

NOTE: STENCIL TO BE 0.15 [.006] THICK. 0.635±0.100[.0250±.0039] (TYP)

PIN 2

PIN 80

7AB

POSITION

PIN 79

PIN 79

PIN 79

PIN 79

- 0.400[.0157] (TYP)


DESIGNED & DIMENSIONED IN MILLIMETERS [INCHES]

TABLE 4

POSITION "A"

-10 5.72[.225]
-20 12.07[.475]
-30 18.42[.725]
-40 24.77[.975]

-40 POSITION SHOWN
(USE FOR 10, 20, 30 & 40 POSITIONS)



NOTE:

STENCIL TO BE 0.15 [.006] THICK.

TABLE 3						
POSITION "A" "B" "C'						
-50	34.29[1.350]	30	19.05[.750]			
-60	40.64[1.600]	36	22.86[.900]			
-70	46.99[1.850]	42	26.67[1.050]			

-50 POSITION SHOWN (USE FOR 50, 60 & 70 POSITIONS)


PROPRIETARY NOTE


THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.




DESIGNED & DIMENSIONED IN MILLIMETERS [INCHES]

TABLE 5					
POSITION	"A"	"B"	"C"	"D" ±.076[.003]	
-10	5.715[.2250]	N/A	N/A	7.788[.307]	
-20	12.065[.4750]	N/A	N/A	14.138[.557]	
-30	18.415[.7250]	N/A	N/A	20.488[.807]	
-40	24.765[.9750]	N/A	N/A	26.838[1.057]	
-50	34.290[1.3500]	30	19.050[.7500]	36.363[1.432]	
-60	40.640[1.6000]	36	22.860[.9000]	42.70[1.681]	
-70	46.990[1.8500]	42	26.670[1.0500]	49.05[1.931]	







NOTES:

- 1. © REPRESENTS A CRITICAL DIMENSION.
 2. -10, -20 AND -30 CARDS HAVE NO SLOT.
 3. ALL DIMENSIONS ARE SYMMETRIC ABOUT THE CENTERLINE.
 4. PLATING TO BE .000030 INCHES GOLD WITH A HARDNESS OF 120-200 KNOOPS.
- **F** 5. FOR PROPER CONTACT REGISTRATION, PLATING BUS TIE TO BE THE WIDTH OF THE EDGE FINGER.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN
CONSENT OF SAMTEC, INC.



PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com code: 5532:

code: 55322 -SHEET 3 OF 3