







APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/14/13	
A		ADDED & REVISED DIM.	8/19/13	
B		UPDATED DRAWING	8/30/16	HR/CH
C		INCREASED TERM TO INS RETENTION	1/13/17	HR/CH



SECTION A-A



RECOMMENDED
PANEL CUT-OUT

SPECIFICATIONS:

Material:
 Insulator: Nylon66, rated UL 94V-0
 Insulator color: Black
 Contacts: Copper Alloy
 Plating:

Tin over Copper underplate overall
 Electrical:

Rating: 15A, 125V (C-ULus)
 Insulation resistance: 100 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 3,000 VAC for 1 minute
 Environmental:
 Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES HOLES .X ± .10 Ø.X ±.10 .XX ± .020 Ø.XX ±.015 .XXX ± .015 Ø.XXX ±.010			ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710		
APPROVALS			TITLE		
DATE			NEMA RECEPTACLE		
DRAWN	AY	3/14/13			
CHECKED	YC	3/14/13			
APPROVED					
			SIZE X	PART NO. NEMA-5-1-A	
			REF: S00087C	SCALE: NTS	SHEET 1 OF 1
			REV. C		