

**MODEL:** PJ-011B | **DESCRIPTION:** DC POWER JACK**FEATURES**

- 2.5 mm center pin
- 5.0 A rating
- vertical orientation
- threaded panel mount

**SPECIFICATIONS**

| parameter                       | conditions/description | min | typ   | max | units  |
|---------------------------------|------------------------|-----|-------|-----|--------|
| rated input voltage             |                        |     | 24    |     | Vdc    |
| rated input current             |                        |     |       | 5.0 | A      |
| contact resistance <sup>1</sup> |                        |     |       | 30  | mΩ     |
| insulation resistance           | at 500 Vdc             | 100 |       |     | MΩ     |
| voltage withstand               | for 1 minute           |     |       | 500 | Vac    |
| insertion/withdrawal force      |                        | 0.3 |       | 3   | kg     |
| operating temperature           |                        | -25 |       | 70  | °C     |
| life                            |                        |     | 5,000 |     | cycles |
| flammability rating             | UL94V-0                |     |       |     |        |
| RoHS                            | yes                    |     |       |     |        |


Note: 1. When measured at a current of less than 100 mA/1 kHz

**SOLDERABILITY**






| parameter      | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for 3~5 seconds        |     |     | 360 | °C    |

MECHANICAL DRAWING

units: mm[inches]  
tolerance: ±0.3 mm  
unless otherwise noted



| DESCRIPTION | MATERIAL              | PLATING/COLOR |
|-------------|-----------------------|---------------|
| center pin  | brass                 | nickel        |
| terminal 1  | brass t=0.4           | silver        |
| terminal 2  | phosphor bronze t=0.2 | silver        |
| terminal 3  | brass t=0.3           | silver        |
| nut         | brass                 | nickel        |
| insulator   | bakelite t=1.0        | natural       |
| plastic     | PBT+30%GF [UL94V-0]   | black         |



MATING PLUG  
Jack Insertion Depth: 9.0 mm

|            |         |
|------------|---------|
| SCHEMATIC  |         |
| Model      | PJ-011B |
| Center Pin | Ø2.5 mm |

Note: 1. All specifications measured at 10~35°C, humidity at 45~85%, under standard atmospheric pressure, unless otherwise noted.

REVISION HISTORY

| rev. | description                       | date       |
|------|-----------------------------------|------------|
| 1.0  | initial release                   | 04/17/2006 |
| 1.01 | pin positions updated             | 05/01/2008 |
| 1.02 | model revised                     | 05/12/2008 |
| 1.03 | hole cutout dimensions added      | 06/27/2011 |
| 1.04 | applied new spec template         | 11/01/2013 |
| 1.05 | brand update                      | 06/02/2020 |
| 1.06 | logo, datasheet style update      | 08/05/2022 |
| 1.07 | changed housing material          | 06/26/2023 |
| 1.08 | CUI Devices rebranded to Same Sky | 09/12/2024 |

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[sameskydevices.com](https://www.sameskydevices.com)