

Additional Resources: Product Page | 3D Model | PCB Footprint

date 09/12/2024

page 1 of 3

# SERIES: SJ1-351XN | DESCRIPTION: AUDIO JACK


#### **FEATURES**

- · right angle
- · non-threaded
- · metal bushing





### **PART NUMBER KEY**



### **SPECIFICATIONS**


parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	А
contact resistance	between terminal and mating plug between terminal in a closed circuit			50 30	$m\Omega$
insulation resistance	at 500 Vdc	100			МΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-O				
RoHS	yes				


### **SOLDERABILITY**

parameter	conditions/description	min	typ	max	units
wave soldering	dipped in solder pot for 5 ±0.5 seconds	255	260	265	°C


## **MECHANICAL DRAWING**


units: mm tolerance: X.X ±0.50 mm X.XX ±0.30 mm X.XXX ±0.15mm PCB: ±0.05 mm unless otherwise specified








DESCRIPTION	MATERIAL	PLATING/COLOR
terminal 1	brass t=0.3	silver over nickel
terminal 2	copper alloy t=0.25	silver over nickel
terminal 3	copper alloy t=0.25	silver over nickel
terminal 4	brass t=0.3	silver over nickel
terminal 5	brass t=0.3	silver over nickel
bushing	brass	nickel
cover	PBT (UL94V-0)	black
housing	PBT (UL94V-0)	black
•		












Recommended PCB Layout Top View



Model No.	SJ1-3513N	SJ1-3514N	SJ1-3515N
Schematic	01 03 03	°1 °3 °4 °2	01 03 05 04 02
PIN			
1	sleeve	sleeve	sleeve
2	tip	tip	tip
3	ring	ring	ring
4	NP	tip switch	tip switch
5	NP	NP	ring switch

### **REVISION HISTORY**

rev.	description	date	
1.0	initial release	09/09/2006	
1.01	new template applied	02/27/2012	
1.02	changed top cover to PBT	04/19/2017	
1.03	changed terminal plating to silver	02/12/2019	
1.04	brand update	10/09/2019	
1.05	product reengineered for improved manufacturability and production yield, see PCN for details	06/30/2023	
1.06	product reengineered for improved manufacturability and production yield, see PCN for details	07/19/2024	
1.07	CUI Devices rebranded to Same Sky	09/12/2024	

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.