




1/2" (12.7 mm) Conductive Plastic and Cermet Potentiometer



FEATURES

- Robust construction
- High rotational life (50 000 cycles)
- Up to three sections PC support plates
- Rotary switches and solder lug terminals available
- Tests according to CECC 41000 or IEC 60393-1
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

RoHS
COMPLIANT

LINKS TO ADDITIONAL RESOURCES



QUICK REFERENCE DATA

| | |
|-------------------------|---|
| Multiple module | Up to 3 modules |
| Switch module | Yes |
| Detent module | n/a |
| Special electrical laws | A: linear, L: logarithmic, F: reverse logarithmic |
| Sealing level | IP 64 |
| Lifespan | 50K cycles |

148 FEATURES


- Conductive plastic element
- Quiet electrical output

149 FEATURES


- Cermet element
- Low temperature coefficient (± 150 ppm/ $^{\circ}$ C)

DIMENSIONS in millimeters (inches) ± 0.5 mm (± 0.02 ")


Single, dual or triple




Solder lug terminals



Front and rear support plates E = flush with board surface



| ELECTRICAL SPECIFICATIONS | | |
|--|--|--------------------------------|
| PARAMETER | 148 | 149 |
| Resistance range | linear | 1 k Ω to 500 k Ω |
| | non-linear | 500 Ω to 250 k Ω |
| Tolerance | linear | 10 % |
| | non-linear | 20 % on request 10 % |
| Linearity (typical) | ± 5 % independent | |
| End resistance | 4 Ω maximum each end | |
| Power rating | 0.5 W at 70 °C 0 W at 120 °C | 1 W at 70 °C 0 W at 150 °C |
| | Non-linear or PC mount, derate 50 % | |
| Circuit diagram |  | |
| Effective rotation | 270° \pm 10° without rotary switch 240° \pm 10° with rotary switch | |
| Contact resistance variation (typical) | 1.5 % of total resistance | 3 % of total resistance |
| Maximum continuous working voltage | 350 V _{AC} across end terminals, but within power rating | |
| Dielectric withstanding voltage | Sea level -750 V _{AC} | |

| MECHANICAL SPECIFICATIONS | | |
|----------------------------------|--|------------------|
| Mechanical travel | 300° \pm 5° | |
| Operating torque (typical) | Single section 0.2 oz. to 3.0 oz. - in dual or triple section 0.3 oz.-inch to 4.5 oz.-inch | |
| End stop torque | bushing A and B | 2.1 lb-inch max. |
| | bushing F | 6.8 lb-inch max. |
| Weight (approx.) | single | 0.19 oz. |
| | dual | 0.27 oz. |
| | triple | 0.35 oz. |
| Terminals | electrical elements | e3: pure Sn |
| | switch elements | e4: gold plated |

| ENVIRONMENTAL SPECIFICATIONS | | |
|--|---------------------------------------|---------------------------------------|
| | 148 | 149 |
| Operating temperature | -40 °C to +125 °C | -40 °C to +125 °C |
| Storage temperature | -55 °C to +125 °C | -55 °C to +125 °C |
| Temperature cycling (5 cycles) | -40 °C to +125 °C (4 % ΔR_T) | -40 °C to +125 °C (3 % ΔR_T) |
| Load life (1000 h rated load at 70 °C) | 10 % ΔR_T | 5 % ΔR_T |
| Mechanical endurance | 50 000 cycles | |
| TCR (typical) | ± 500 ppm/°C | ± 150 ppm/°C |
| Sealing | IP64 | |

Note


- Nothing stated herein shall be construed as a guarantee of quality or durability

| MARKING | |
|--|--|
| Vishay logo, SAP code of ohmic value, tolerance in %, variation law, manufacturing date (four digits), "3" for the lead 3, product series (148, 149) | |

LOCATING PEGS (anti-rotation lug)

The locating peg is provided by a plate mounted on the bushing and positioned by the module sides. Four set positions are available, clock face orientation: 12, 3, 6, 9.


All 148, 149 bushings have a double flat. When panel mounting holes have been punched accordingly, an anti-rotation lug is not necessary.



| CODE | VERSION | BUSHING A, B | BUSHING F | EFFECTIVE HIGH PEG |
|------|---------|--------------|-----------|--------------------|
| A | Ø d mm | 2 | 2 | 0.7 |
| | L mm | 6.2 | 6.2 | - |
| B | Ø d mm | 2 | 2 | 0.7 |
| | L mm | 7.75 | 7.75 | - |
| C | Ø d mm | - | 3.5 | 1.1 |
| | L mm | - | 13.5 | - |

Locating pegs are supplied in separate bags with nuts and washers

RSID OPTION: ROTARY SWITCH MODULES



- Rotary switches
- Current up to 2 A
- SPDT: single pole, changeover switch in CCW position - 3 pins
- Sealing IP60

MODULES: RS ON/OFF SWITCH RSI CHANGEOVER SWITCH

The position of each module is free.

RS and RSI rotary switches are housed in a standard 148, 149 module size 12.7 mm x 12.7 mm x 5.08 mm (0.5" x 0.5" x 0.2"). They have the same terminal styles as the assembled electrical modules.

An assembly can comprise 1 or more switch modules.

Switch actuation is described as seen from the shaft end.
D: means actuation in maximum CCW position

The switch actuation travel is 25° with a total mechanical travel of 300° ± 5° and electrical travel of electrical modules is 238° ± 10°.

RSID Single Pole CHANGEOVER


In full CCW position, the contact is made between 3 and 2 and open between 3 and 1. Switch actuation (CW direction) reverses these positions.

SWITCH SPECIFICATIONS

| | | |
|--|----------------------|--------------------------------|
| Switching power maximum | | 62.5 VA v 15 VA = |
| Switching current maximum | | 0.25 A 250 V v 0.5 A 30 V = |
| Maximum current through element | | 2 A |
| Contact resistance | | 100 mΩ |
| Dielectric strength | Terminal to terminal | 1000 V _{RMS} |
| | Terminal to bushing | 2000 V _{RMS} |
| Maximum voltage operation | | 250 V v 30 V = |
| Insulation resistance between contacts | | 10 ⁶ MΩ |
| Life at P _{max.} | | 10 000 actuations |
| Minimal travel | | 25° |
| Operating temperature | | -40 °C to +85 °C |

ELECTRICAL DIAGRAM

RSID CCW POSITION



Note

(1) Common

**ORDERING INFORMATION** (part number)

| | | | | | | | | | | | | | | | | | |
|--|-------------------|---|-----------------------------------|------------------------|----------------------------|---|----------------------|--|----------------------|--|---|---|---|---|---|---|---|
| 1 | 4 | 8 | 1 | 0 | F | 0 | G | J | S | X | 1 | 0 | 1 | 0 | 3 | K | A |
| MODEL | NUMBER OF MODULES | | SWITCH | BUSHING | LOCATING PEG | | SHAFT | SHAFT END | LEADS | RESISTANCE CODE / TOLERANCE / TAPER OR SPECIAL | | | | | | | |
| 148 = plastic conductive 149 = cermet element | 1 2 3 | | 1 = RSID 0 = without switch | See table "Bushing" | 0 = without A B C | | See table "Shaft" | S = slotted On request: R = round F = flattened | See table "Leads" | Resistance code: 101 = 100 Ω to 105 = 1 MΩ Tolerance code: M = 20 %; K = 10 % Taper: A (S); L (Z); F (R) or Special code given by Vishay | | | | | | | |

BUSHING

| | Ø | L | OLD CODES |
|---|------|------|-----------|
| A | 1/4" | 1/4" | N |
| B | 1/4" | 3/8" | J |
| F | 3/8" | 3/8" | G |

LEADS

| | TYPE | PIN SPACING | SPACE BETWEEN MODULES | OLD CODES |
|-----|--------------------------------|---------------------|-----------------------|-----------|
| X10 | PCB pins | 2.54 mm (0.100") | n/a | P |
| X13 | | | 7.62 mm (0.300") | |
| A10 | PCB pins and support plates | 2.54 mm (0.100") | n/a | E |
| A13 | | | 7.62 mm (0.300") | |
| Y00 | Sold, lugs | 4.65 mm (0.183") | n/a | S |
| Y03 | | | 7.62 mm (0.300") | |

SHAFT

| | Ø | FMS | OLD CODES |
|----|------|--------|-----------|
| BB | 1/8" | 1/2" | 32 |
| BG | 1/8" | 5/8" | 40 |
| BH | 1/8" | 3/4" | 48 |
| BJ | 1/8" | 7/8" | 56 |
| GB | 1/4" | 1/2" | 32 |
| GG | 1/4" | 5/8" | 40 |
| GH | 1/4" | 3/4" | 48 |
| GJ | 1/4" | 7/8" | 56 |
| GL | 1/4" | 1" | 64 |
| GN | 1/4" | 1 1/4" | 80 |

PART NUMBER DESCRIPTION (for information only)

| | | | | | | | | | | | | | | |
|-------|---------|--------|---------|-----------------|-------|-------|-------|-------|-------|------|-------|---------|---------|----------------|
| 148 | 1 | 0 | F | 0 | GJ | S | X10 | BO50 | 10K | 10 % | A | | | e3 |
| MODEL | MODULES | SWITCH | BUSHING | LOCATING PEG | SHAFT | SHAFT | LEADS | PACK. | VALUE | TOL. | TAPER | SPECIAL | SPECIAL | LEAD FINISH |

ACCESSORIES

| | |
|--|--|
| Additional Accessories (to order separately) | www.vishay.com/doc?51051 |
| Control knobs | www.vishay.com/doc?51101 |

RELATED DOCUMENTS

| APPLICATION NOTES | |
|--|--|
| Potentiometers and Trimmers | www.vishay.com/doc?51001 |
| Guidelines for Vishay Sernice Resistive and Inductive Components | www.vishay.com/doc?52029 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.