

6

5

4

3

2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev

AWO #

Description

Date

Appr

-

RELEASED

3/13/20

D

D

C


C

B




B

A

A



RECOMMENDED P.C.B. LAYOUT



SPECIFICATIONS:

Material:

Housing: Hi-Temp Thermoplastic, rated UL94V-0

Housing Color: White

Contact: Phosphor Bronze, Gold Plated

Electrical:

Contact resistance: 30 Milliohms max

Insulation resistance: 1,000 Megaohms ohms min

Dielectric Voltage: 500 VAC one sec level

Temperature Rating:

Operating temperature: -25°C to +85°C.

Environmental:

Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED
MM ANGLE
X ± 0.30 X ± 1°
X.X ± 0.25 X.X ± 0.5°
X.XX ± 0.20
X.XXX ± 0.10

APPROVALS

DATE

DRAWN

LH

3/13/20

CHECKED

MY

3/13/20

APPROVED

ADAM
TECH
INTERCONNECTS

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE

BATTERY COIN CELL HOLDER, CR 2032
WHITE COLOR, SMT TYPE, GOLD PLATED

SIZE

X

PART NO.

BH-27A-5-G-WT

REV.

-

REF: S00136C

SCALE: NTS

SHEET 1 OF 1

6

5

4

3

2

1