

6

5

4

3


2

1




APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/25/20	



RECOMMENDED PCB LAYOUT



SPECIFICATIONS:

Material:

Housing: Hi-temp thermoplastic, rated UL 94V-0 Color: White

Contact: Phosphor Bronze, Gold over Nickel Underplated

Electrical:

Contact resistance: 30 mohms max

Insulation resistance: 1,000 Megaohms ohms min

Dielectric Voltage: 500 VAC one sec level

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED

MM	ANGLE
X ± 0.30	X ± 1°
X.X ± 0.25	X.X ± 0.5°
X.XX ± 0.20	
X.XXX ± 0.10	

APPROVALS		DATE
DRAWN	LH	3/25/20
CHECKED	MY	3/25/20
APPROVED		

ADAM
TECH
INTERCONNECTS

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE

COIN CELL HOLDER, CR 2450, PCB MOUNT

SIZE	PART NO.	REV.
X	BH-78B-5	-
REF: S00136C		SCALE: NTS
		SHEET 1 OF 1

6

5

4

3

2

1