



Multi-Device Charging Station, 48 USB Ports, iPad and Android Tablets, White

MODEL NUMBER: CS48USBW











Locking steel cabinet provides 2.4A USB charging, syncing, secure storage and cord management for up to 48 tablets and other USB devices.

Features

Multi-Device Charging Station Accommodates up to 48 iPads and Other Tablets

The 120V CS48USBW provides USB charging, device syncing, secure storage and cord management for as many as 48 iPad, Android, Surface, Kindle and other USB tablets, smartphones and devices. The connected devices' chargers connect to the charging station's 48 USB ports, which provide the fastest charging supported by each device up to 2.4A per port.

Locking Steel Enclosure Keeps Valuable Equipment Safe and Secure

Constructed from heavy-duty steel covered with a powder-coated finish, this tablet charging station provides safe, secure storage. Doors lock with the included keys to help prevent theft, damage and tampering. Flow-through ventilation helps protect against overheating, and the specially coated shelves help prevent device scratches and scuffs.

Supports Convenient Syncing

The USB sync uplink port connects to a host computer for wired or wireless syncing. The CS48USBW can sync and charge devices at the same time, up to 1.5A charging per port during wired syncing.

Comes Fully Assembled for Immediate Use

The CS48USBW ships fully assembled and supports mounting to a wall, desk, table, counter or floor. The front door opens 180 degrees to allow full access to the interior. Removable dividers accommodate thicker USB devices. A firmware upgrade port allows future updates. To move the charging station from room to room, you may convert it to a mobile cart using the optional CSHANDLEKIT accessory (sold separately). A detachable 10-foot (3.1-meter) power cord with NEMA 5-15P plug connects the charging station to an available AC outlet.

Specifications

OVERVIEW	
UPC Code	037332188960
Product Type	Multi-Device Charger

Highlights

- 48 internal USB ports provide up to 2.4A apiece for fast charging of tablets
- Sturdy steel construction with locking doors that help prevent theft or tampering
- Supports charging of iPad, Android, Surface, Kindle and other USB tablets
- Flow-through ventilation helps prevent connected tablets from overheating
- 10 ft. cord with NEMA 5-15P plug allows great flexibility in reaching AC outlets

Package Includes

- CS48USBW Multi-Device Charging Station, White
- Detachable AC input cord with NEMA 5-15P plug, 10 ft. (3.1 m)
- (2) Keys
- Owner's manual





Charger Functions Charger, Secure; Sync	Charging Form Factor	Stationary Cabinet	
Device Compatibility Tablet, Phone Device Slotes 48 INPUT Neminal Input Voltage(e) Supported 420 VAC; 230 VAC Voltage Compatibility (VAC) 110-240 Input Frequency 50 / 60 Hz (auto-select) Input Cord Length (th) 10 Input Cord Length (th) 3.05 POWER POWER <th c<="" td=""><td></td><td></td></th>	<td></td> <td></td>		
New Power			
Nominal Input Voltage(s) Supported 120V AC; 230V AC 100-240			
Nominal Input Voltage(s) Supported 120V AC: 230V AC Voltage Compatibility (VAC) 110-240 Input Frequency 50 / 60 Hz (auto-select) Input Plug Type NEMA 5-15P Input Cord Length (tt) 10 Input Cord Length (m) 3.05 OUTPUT Frequency Compatibility 50 / 60 Hz POWER FOWER Power Consumption (Watts) 224 CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Poteatial Pass through Charging Ports Amps (48) 2.4A Charging Ports Amps 4.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (thwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensio	Device diots		
Voltage Compatibility (VAC) 110-240 Input Frequency 50 / 60 Hz (auto-select) Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 OUTPUT Frequency Compatibility 50 / 60 Hz POWER Power Consumption (Watts) 224 CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Potealis Pass through Charging Ports Potealis Pass through Charging Ports Amps per Pot 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (ftwd / cm) 41.02 x 28.35 x 26.38 Shipping Dimensions (ftwd / cm) 191.00	INPUT		
Input Frequency 50 / 60 Hz (auto-select) Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 OUTPUT Frequency Compatibility 50 / 60 Hz POWER FOWER FOWER CHARGING A8 Charging Ports A8 Total Charging Mmps 120A Total Charging Watts 600 Charging Port Type USB A (FEMALE) Charging Port Subtails Pass through Charging Ports Details Pass through Charging Ports / Amps (48) 2-4A Overcharge Protection Yes Charging Amps per Port 2-4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / rm) 104.19 x 72.01 x 67.01 Shipping Dimensions (hwd / rm) 104.19 x 72.01 x 67.01	Nominal Input Voltage(s) Supported	120V AC; 230V AC	
Input Plug Type NEMA 5-16P Input Cord Length (ft.) 10 COUTPUT Frequency Compatibility 50 / 60 Hz Fower POWER Fower Consumption (Watts) 224 CHARGING Number of Charging Ports 48 Total Charging Amps 120A Charging Watts 600 Charging Port Oye USB A (FEMALE) Charging Port Details Pass through Charging Ports Details Pass through Charging Ports (Amps (48) 2-4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / m) 104.19 x 72.01 x 67.01 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Voltage Compatibility (VAC)	110-240	
Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 OUTPUT Frequency Compatibility 50 / 60 Hz POWER POWER CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Port So Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Ves Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Input Frequency	50 / 60 Hz (auto-select)	
Input Cord Length (m) output Frequency Compatibility 50 / 60 Hz Fower Consumption (Watts) 224 CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Useight (lbs.) 191.00	Input Plug Type	NEMA 5-15P	
OUTPUT Fequency Compatibility 50 / 60 Hz POWER POWER Consumption (Watts) 224 CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Input Cord Length (ft.)	10	
Frequency Compatibility 50 / 60 Hz POWER POWER CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Wethod USB Charging Port Type USB A (FEMALE) Charging Ports Potalis Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Input Cord Length (m)	3.05	
Frequency Compatibility 50 / 60 Hz POWER POWER CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Wethod USB Charging Port Type USB A (FEMALE) Charging Ports Potalis Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00			
Power Consumption (Watts) 224 CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Petalis Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00			
CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Frequency Compatibility	50 / 60 Hz	
CHARGING Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Weight (lbs.) 191.00	POWER		
Number of Charging Ports 48 Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00 Has a Color William Color (has a Color Color) Shipping Weight (lbs.) 191.00	Power Consumption (Watts)	224	
Total Charging Amps 120A Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00	CHARGING		
Total Charging Watts 600 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00	Number of Charging Ports	48	
Charging Method USB (FEMALE) Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00	Total Charging Amps	120A	
Charging Port Type USB A (FEMALE) Charging Ports Details Pass through Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00 Shipping Weight (lbs.) 191.00	Total Charging Watts	600	
Charging Ports Details Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Pass through (48) 2.4A Yes Color White At 1.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 191.00	Charging Method	USB	
Charging Ports / Amps (48) 2.4A Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Charging Port Type	USB A (FEMALE)	
Overcharge Protection Yes Charging Amps per Port 2.4A PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Charging Ports Details	Pass through	
Charging Amps per Port PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Charging Ports / Amps	(48) 2.4A	
PHYSICAL Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Overcharge Protection	Yes	
Color White Material of Construction Steel Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Charging Amps per Port	2.4A	
Material of Construction Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.)	PHYSICAL		
Charging Station Form Factor Stationary Cabinet Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Color	White	
Shipping Dimensions (hwd / in.) 41.02 x 28.35 x 26.38 Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Material of Construction	Steel	
Shipping Dimensions (hwd / cm) 104.19 x 72.01 x 67.01 Shipping Weight (lbs.) 191.00	Charging Station Form Factor	Stationary Cabinet	
Shipping Weight (lbs.) 191.00	Shipping Dimensions (hwd / in.)	41.02 x 28.35 x 26.38	
	Shipping Dimensions (hwd / cm)	104.19 x 72.01 x 67.01	
Shipping Weight (kg) 86.64	Shipping Weight (lbs.)	191.00	
	Shipping Weight (kg)	86.64	





Slot Dimensions - Bottom (hwd / in.)	$8.0 \times 0.8 \times 13.9$	
Slot Dimensions - Bottom (hwd / mm)	204 x 20,1 x 353.8	
Slot Dimensions - Middle (hwd / in.)	8.0 x 0,8 x 13,9	
Slot Dimensions - Middle (hwd / mm)	204 x 20,1 x 353.8	
Slot Dimensions - Top (hwd / in.)	8.1 x 0,8 x 13,9	
Slot Dimensions - Top (hwd / mm)	206 x 20,1 x 353.8	
Unit Dimensions (hwd / in.)	35.630 x 23.620 x 21.570	
Unit Dimensions (hwd / cm)	90,42 x 59,9 x 54,86	
Unit Weight (lbs.)	150	
Unit Weight (kg)	68.04	
Number of Shelves	3	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	
Built-In Circuit Breaker	Yes	
Cord Management	Yes	
Overcurrent Protection	Yes	
EMI/RFI Line Noise Protection	Yes	
Flow-Through Ventilation	Yes	
IP68 Rated	No	
IP20 Rated	No	
UV Sterilization	No	
Locking	Yes	
Lock Type	Key	
STANDARDS & COMPLIANCE		
Product Certifications	NOM (Mexico); UL 60950-1	
Product Compliance	RoHS; CE (Europe); EIA/ECA-310-E; REACH; FCC Part 15 Class B (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	2-year limited warranty	
CATEGORY PAGE FILTERS (Y/N ONLY)		
External Receptacle	No	





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.