

TRIPP LITE SERIES

45-Device AC Mobile Charging Cart - Laptops and Chromebooks, 120V, NEMA 5-15P, 10 ft. (3.05 m) Cord, Black

MODEL NUMBER: CSC45AC



Charges, secures and organizes up to 45 Chromebooks and laptops in education, healthcare, retail, warehouse and office environments.

Features

Mobile Charging Cart Accommodates up to 45 Chromebooks and LaptopsThis 120V charging cart provides timed AC charging, secure storage and cord management for as many as 45 Chromebooks and laptops. The connected devices' AC adapters plug into 45 NEMA 5-15R outlets, which provide up to 1,440 watts for charging. A built-in circuit breaker protects the devices against overloads.

High-Speed Zone Charging Conserves Energy and Helps Avoid Potential OverloadsThe 45 NEMA 5-15R outlets are split into two color-coded charging zones to support more devices and higher wattages without overloads. A built-in timer alternates charging zones every hour. LEDs indicate which zone is being charged at any given time.

Locking Steel Enclosure Keeps Valuable Equipment Safe and SecureConstructed from heavy-duty steel covered with a black powder-coated finish, this laptop charging cart provides safe, secure storage. Devices and their power adapters are stored in separate compartments. The front and back doors lock with the included keys to help prevent theft, damage and tampering. For extra security, the front door can be fastened with a user-supplied padlock. Flow-through ventilation helps protect against overheating, and the specially coated shelves help prevent device scratches and scuffs.

Moving Your Devices from Room to Room Is EasyLarge swivel casters with non-marking wheels improve the ride over uneven surfaces and lock to help prevent unwanted movement. The reversible wide-grip handle makes the cart easy to control. Corner safety bumpers protect walls and doorways from scratches. The compact Chromebook charging cart takes up about the same amount of physical space as a typical A/V cart.

Well-Organized to Avoid Confusing Cable ClutterHeavy power adapters store out of the way in removable baskets. Cables and connectors run through zoned slots and an overhead cable manager, keeping them organized and out of the way. Adjustable dividers accommodate up to 15 devices per shelf, and device spaces are numbered for easy identification. A power cord wrap keeps the input cord out of the way when moving the charging station. The 10-ft. (3.05 m) cord with space-saving right-angle NEMA 5-15P plug allows great flexibility in reaching AC outlets.

Laminated Wood-Grain Top Doubles as a Convenient WorkstationThe laminated top acts as a smooth writing surface and holds a projector, monitor or other peripherals that plug into two external

Highlights

- 45 internal NEMA 5-15R outlets provide up to 1,440 total watts for charging
- Hourly timer alternates charging zones to help prevent overloads
- In-cabinet RJ45 jack connects Ethernet peripherals, including routers and hotspots
- Dual external NEMA 5-15R outlets provide power for a monitor or projector
- 10-ft. (3.05 m) cord with NEMA 5-15P plug allows great flexibility in reaching AC outlets

Applications

- Charge up to 45 Chromebooks and laptops in schools, businesses and government organizations that rely on the daily use of mobile devices
- Easily and safely transport connected devices from room to room
- Use the laminate top as a workstation or a sturdy platform for A/V equipment

Package Includes

- CSC45AC 45-Device AC Charging Station Cart, Black
- Cart handle
- Input cord wrap
- (6) Protective bumpers
- (10) Hex screws
- Hex key
- (2) Keys
- Owner's manual



NEMA 5-15R outlets controlled by an inside on/off switch. A pass-through RJ45 jack is provided for connecting Ethernet devices, such as a wireless router or hotspot, inside the cabinet.

Specifications

| OVERVIEW | |
|------------------------------------|-----------------------|
| UPC Code | 037332226082 |
| Product Type | Multi-Device Charger |
| Charging Form Factor | Mobile Cart |
| Charger Functions | Charge; Secure |
| Device Compatibility | Chromebook; Laptop |
| Device Slots | 45 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Voltage Compatibility (VAC) | 120 |
| Input Frequency | 60 Hz |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 10 |
| Input Cord Length (m) | 3.05 |
| OUTPUT | |
| Frequency Compatibility | 60 Hz |
| CHARGING | |
| Number of Charging Ports | 45 |
| Charging Method | AC |
| Charging Port Type | NEMA 5-15R |
| Charging Ports Details | Pass through |
| Charging Ports / Amps | (45) 12A |
| Overcharge Protection | No |
| Charging Amps per Port | 12A |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Steel |
| Charging Station Form Factor | Mobile Cart |
| Shipping Dimensions (hwd / in.) | 46.85 x 26.77 x 29.13 |





| Skit Dimensions - Bottom (twd / in.) 10.11 x 1.14 x 15.58 Skit Dimensions - Bottom (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Middle (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Middle (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Top (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Top (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Top (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Top (twd / in.) 10.13 x 1.14 x 15.58 Skit Dimensions - Top (twd / in.) 10.13 x 2.14 x 15.58 Skit Dimensions (twd / on.) 10.35 x 68.14 x 73.25 (con la manja instalada) Unit Utimensions (twd / on) 109.35 x 66.14 x 73.25 (con la manja instalada) Unit Weight (bs.) 47.50 Unit Weight (bs.) 47.50 Kasembly Required Yes Cord Management Yes Cord Management Yes Cord Management Yes Cord Management Yes Page Rated No IP20 Rated No IP20 Rated No IP20 Rated No | Shipping Weight (kg) | 90.72 | |
|---|--------------------------------------|--|--|
| Silo Dimensions - Bottom (Itwd / mm) 266.9 × 29.17 × 395.72 Sot Dimensions - Middle (Itwd / mi) 10.13 × 1.14 × 15.58 Sot Dimensions - Top (Itwd / mi) 257.3 × 29.17 × 395.72 Sot Dimensions - Top (Itwd / mi) 257.3 × 29.17 × 395.72 Sot Dimensions - Top (Itwd / mi) 257.3 × 29.17 × 395.72 Unit Dimensions (Itwd / mi) 40.905 × 26.04 × 28.40 Unit Dimensions (Itwd / mi) 40.905 × 26.04 × 28.40 Unit Dimensions (Itwd / mi) 109.35 × 66.14 × 73.25 (con Is manja instalada) Unit Weight (Itb.) 147.50 Unit Weight (Itb.) 147.50 Namber of Shelves 3 Assembly Required Yes FETURES & SPECIFICATIONS Ves Ourid Mangement Yes Ord Management Yes Overcurren Protection Yes REMURE Lie Hokise Protection No IVPS Henkization Yes IVPS Henkization Yes IVPS Henkization Yes IVPS Henkization Yes IVPS Henkization No IVPS Henkization No < | | | |
| mm) ADD ANSI ANSI AND | | 10.11 X 1.14 X 15.58 | |
| Slot Dimensions - Middle (hvd / m) 257.3 x 29.17 x 395.72 Slot Dimensions - Top (hvd / m) 257.3 x 29.17 x 395.72 Unit Dimensions (hvd / m) 257.3 x 29.17 x 395.72 Unit Dimensions (hvd / m) 43.050 x 26.040 x 28.840 Unit Dimensions (hvd / m) 19.36 x 66.14 x 73.25 (con la manija instalada) Unit Weight (bb.) 147.50 Unit Weight (bb.) 66.90 Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS Yes Antimicrobial No Built-In Circuit Breaker Yes Cord Managemant Yes Overcurrent Protection Yes Plow-Through Ventilation No Plow-Through Ventilation Yes UV Sterilization No UV Sterilization No Locking Yes Product Centifications CANCSA-C222 No. 60960-1 (Canada); NOM (Maxico); UL 60960-1 Verserum Protection RoHzes CELVERON; CE Leurope; REACH; FCC (USA) Warranty Period Ryear limited warranty | | 256.9 x 29.17 x 395.72 | |
| Silot Dimensions - Top (twd / n.) 10.13 x 1.14 x 15.58 Silot Dimensions - Top (twd / m.) 257.3 x 29.17 x 395.72 Unit Dimensions (twd / m.) 43.050 x 26.040 x 28.840 Unit Dimensions (twd / m.) 190.95 x 66.14 x 73.25 (con la manija instalada) Unit Weight (tbs.) 147.50 Unit Weight (tbs.) 66.90 Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATONS Antimicrobial Antimicrobial No Built-In Circuit Breaker Yes Cord Management Yes Cord Management Yes EMIRET Line Noise Protection No Ploa Rated No UV Steriization No UV Steriization No Locking Yes StatDACS & COMPLIANCE Yes Product Certifications CAN/CSA-C222 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Vareanty & Support Zeyaer limited warranty Product Gertifications CAN/CSA-C222 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Vareanty & Support Zeyaer limited warranty | Slot Dimensions - Middle (hwd / in.) | 10.13 x 1.14 x 15.58 | |
| Slot Dimensions - Top (hw/ r/m) 257.3 x 29.17 x 395.72 Unit Dimensions (hw/ r/m) 43.050 x 26.040 x 28.840 Unit Dimensions (hw/ r/m) 109.35 x 66.14 x 73.25 (con la manija instalada) Unit Weight (bs.) 147.50 Unit Weight (bs.) 147.50 Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS FATURES & SPECIFICATIONS Yes Cord Management Yes Overcurrent Protection Yes Cord Management Yes Powerurent Protection Yes EMIRFI Line Noise Protection No IP68 Rated No IP20 Rated No Uvit Sterilization No Locking Yes STANDARDS & COMPLIANCE Yes Product Certifications CAN/CSA-C22 2 No. 60960-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RelS; CE (Europe); REACH; FCC (USA) WARRALINE & SUPPORT Zyear limited warranty Product Varranty Period 2year limited warranty | Slot Dimensions - Middle (hwd / mm) | 257.3 x 29.17 x 395.72 | |
| Unit Dimensions (hwd / in). 43.050 x 26.040 x 28.840 Unit Dimensions (hwd / cm) 109.35 x 66.14 x 73.25 (con la manija instalada) Unit Weight (bs.) 147.50 Unit Weight (bs.) 147.50 Unit Weight (kg) 66.90 Numbar of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS Features & specifications No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EMIKPE Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No IV Sterilization No ICord Cordinations Co/CSA-C22.2 No.60960-1 (Canada); NOM (Mexico); UL 60950-1 Product Cordinatos CANCSA-C22.2 No.60960-1 (Canada); NOM (Mexico); UL 60950-1 Product Cordinatos CANCSA-C22.2 No.60960-1 (Canada); NOM (Mexico); UL 60950-1 Product Cordinatos CANCSA-C22.2 No.60960-1 (Canada); NOM (Mexico); UL 60950-1 Pro | Slot Dimensions - Top (hwd / in.) | 10.13 x 1.14 x 15.58 | |
| Unit Dimensions (hwd / cm) 109.35 x 66.14 x 73.25 (con la manija instalada) Unit Weight (bs.) 147.50 Unit Weight (kg) 66.90 Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS Antimicrobial No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EMURET Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IV2 Retext Yes STANDARDS & COMPLIANCE Yes Product Certifications CAV/CSA-C22.2 No. 60850-1 (Canada); NOM (Mexico); UL 60950-1 Product Certifications CAV/CSA-C22.2 No. 60850-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance Rels: CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Product Warranty Period 2-year limited warranty | Slot Dimensions - Top (hwd / mm) | 257.3 x 29.17 x 395.72 | |
| Unit Weight (bs.) 147.50 Unit Weight (kg) 66.90 Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS No Built-In Circuit Breaker Yes Cord Management Yes Yes Cord Management Yes Yes Cord Management Yes Yes Overcurent Protection No Yes ElWRFI Line Noise Protection No Flow-Through Ventilation Yes IP20 Rated No IV2 Sterilization No Locking Yes Compliance Forecurent Reverse Steric Compliance Product Compliance CANICSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Note Compliance Forecurent Reverse Steric Compliance Product Compliance Product Marranty Period Syear Imited warranty < | Unit Dimensions (hwd / in.) | 43.050 x 26.040 x 28.840 | |
| Unit Weight (kg) 66.90 Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EMIKFI Line Noise Protection Yes IP68 Rated No IP68 Rated No UV Sterilization Ves StANDARDS & COMPLIANCE Product Compliance Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANT & SUPPORT Product Warranty Period (Vordivelide) Carterer Product Full CER (INC MARTART) | Unit Dimensions (hwd / cm) | 109.35 x 66.14 x 73.25 (con la manija instalada) | |
| Number of Shelves 3 Assembly Required Yes FEATURES & SPECIFICATIONS Image: SpecificAtions Antimicrobial No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EMURFI Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes StatADARDS & COMPLIANCE Yes Product Certifications CANCSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Certifications CANCSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Certifications CANCSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance CANCSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance Canada); NOM (Mexico); UL 60950-1 Warranty Period 2-year Imited warranty Worldwidey 2-year Imited warranty | Unit Weight (Ibs.) | 147.50 | |
| Assembly Required Yes FEATURES & SPECIFICATIONS Antimicrobial No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes Divercurrent Protection No Flow-Through Ventilation Yes IP68 Rated No IP04 Through Ventilation Yes VS terilization No Locking Yes Locking Yes Product Certifications Kay Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANT & SUPPORT Zyear limited warranty Product Warranty Period Zyear limited warranty | Unit Weight (kg) | 66.90 | |
| FEATURES & SPECIFICATIONS Antimicrobial No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EM/RFI Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE RoHS; CE (Europe); REACH; FCC (USA) Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Support Product Warranty Period Product Warranty Period 2-year limited warranty | Number of Shelves | 3 | |
| Antimicrobial No Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EMURFI Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT -year limited warranty Product Warranty Period 2-year limited warranty | Assembly Required | Yes | |
| Built-In Circuit Breaker Yes Cord Management Yes Overcurrent Protection Yes EM/RF1 Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key Product Certifications Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) | FEATURES & SPECIFICATIONS | | |
| Cord Management Yes Overcurrent Protection Yes EMI/RF1 Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE RoH2: CE (Europe); REACH; FCC (USA) Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Rotart Y & SUPPORT Product Warranty Period Product Warranty Period 2-year limited warranty | Antimicrobial | No | |
| Overcurrent Protection Yes EMI/RFI Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) | Built-In Circuit Breaker | Yes | |
| EMI/RFI Line Noise Protection No Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period 2-year limited warranty Product Warranty Period 2-year limited warranty | Cord Management | Yes | |
| Flow-Through Ventilation Yes IP68 Rated No IP20 Rated No IV20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period 2-year limited warranty CATEGORY PAGE FILTERS (YN) Imited warranty | Overcurrent Protection | Yes | |
| IP68 Rated No IP20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty | EMI/RFI Line Noise Protection | No | |
| IP20 Rated No UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty | Flow-Through Ventilation | Yes | |
| UV Sterilization No Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty | IP68 Rated | No | |
| Locking Yes Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Worldwide) 2-year limited warranty | IP20 Rated | No | |
| Lock Type Key STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty CATEGORY PAGE FILTERS (Y/N ONT) | UV Sterilization | No | |
| STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period (Worldwide) Product Varranty Period 2-year limited warranty CATEGORY PAGE FILTERS (Y/N ONLY) Image: Compliance (Y/N ONLY) | Locking | Yes | |
| Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period Product Warranty Period 2-year limited warranty CATEGORY PAGE FILTERS (Y/N ONLY) Product Warranty | Lock Type | Кеу | |
| Product Compliance RoHS; CE (Europe); REACH; FCC (USA) WARRANTY & SUPPORT Product Warranty Period 2-year limited warranty Product Warranty Period 2-year limited warranty Category Page Filters (Y/N ONLY) | STANDARDS & COMPLIANCE | | |
| WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty CATEGORY PAGE FILTERS (Y/N ONLY) | Product Certifications | CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 | |
| Product Warranty Period (Worldwide) 2-year limited warranty CATEGORY PAGE FILTERS (Y/N ONLY) | Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) | |
| Product Warranty Period (Worldwide) 2-year limited warranty CATEGORY PAGE FILTERS (Y/N ONLY) | WARRANTY & SUPPORT | | |
| | Product Warranty Period | 2-year limited warranty | |
| | CATEGORY PAGE FILTERS (Y/N ONLY) | | |
| | External Receptacle | Yes | |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.