

## USB Tablet / Phone Car Charger, 5V 2.4A / 12W

MODEL NUMBER: U280-001-C2



Charge your Tablet and Phone in your car.

### Description

The 2.4A USB Car Charger allows you to quickly and safely charge a USB-powered device and is ideal for ultra-fast charging devices, such as iPads, other tablets and smartphones. This high-quality and ultra-compact charger works with any standard in-vehicle power outlet and features a translucent ring around the USB port that glows blue to indicate power is being passed through to your device. It is a handy tool to keep your devices fully charged and ready to use while you are on the go.

### Features

- High-speed 2.4A USB port for charging devices, including iPads, tablets, eReaders, smartphone's and more
- Works with any 12V DC auto lighter socket
- Use your existing USB cables to charge all devices
- 5V 2.4A USB port

## Specifications

OVERVIEW	
UPC Code	037332184276
Product Type	Car Charger
Charging Form Factor	Direct Plug-In
Device Compatibility	Phone; Tablet; Amazon Kindle
Technology	USB
INPUT	
Nominal Input Voltage(s) Supported	12V DC
Input Connection Type	Automatic Vehicle Cigarette Lighter

### Highlights

- Quickly charges a Tablet or Phone with up to 2.4A of power
- 5V 2.4A USB port

### System Requirements

- Automobile 12V DC Lighter Socket

### Package Includes

- 2.4A Single USB Car Charger



Powering Business Worldwide

TRIPP LITE  
SERIES

Input Plug Type	Car Auxiliary Power Outlet
<b>OUTPUT</b>	
Output Capacity (Watts)	12
Overload Protection	Yes
<b>CONNECTIONS</b>	
Number of Ports	1
Side A - Connector 1	Car Cigarette Lighter
Side B - Connector 1	USB A (FEMALE)
<b>CHARGING</b>	
Number of Charging Ports	1
Total Charging Amps	1.4A
Total Charging Watts	12
Charging Method	USB
Charging Port Type	USB A (FEMALE)
Charging Ports Details	USB-A: 5V 2.4A (12W)
Charging Ports / Amps	(1) 2.4A
Compatible Devices	Laptop; Smartphone; Tablet
<b>PHYSICAL</b>	
Color	White
Shipping Dimensions (hwd / in.)	1.00 x 4.10 x 6.10
Shipping Dimensions (hwd / cm)	2.54 x 10.41 x 15.49
Shipping Weight (lbs.)	0.06
Shipping Weight (kg)	0.03
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-40° to 176°F (-40° to 80°C)
Operating Humidity Range	20 to 90% RH, Non-Condensing
Storage Humidity Range	5 to 95% RH, Non-Condensing
<b>FEATURES &amp; SPECIFICATIONS</b>	
GaN Technology	No
Overcurrent Protection	Yes



Powering Business Worldwide

TRIPP LITE  
SERIES

Overvoltage Protection	Yes
STANDARDS & COMPLIANCE	
Product Compliance	CE (Europe); FCC (USA); RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.