



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 6720°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE
BF3228-21B	x = .315 y = .295	1190	475	5 ± 1	28,000 ± 10%	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

				METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
		THIRD ANGLE PROJECTION				TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
C CHANGE LEAD LENGTH TO 15±2 B ELECTRICAL RATING CHANGES A BRIGHTNESS RATING CHANGES RELEASED		1/28/20 8/5/04 8/20/97 12/95	DRAWN BY L. WENGSTROM	APPV'D BY S.N.	DATE 1/28/20	SIZE A	FSCM NO. 55335	DRAWING NO. BF3228-21B		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
						NONE	12/95	1/28/20	C	1 OF 1