

JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 8800°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE
BF3380-24B	x = .285 y = .278	1975	790	5 ± 1	28,000 ± 10%	40,000

<sup>\*</sup> RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

				T				_			
			METRIC	DIMENSIO			IKI	[]			
			<del>  (1)                                   </del>	TOLERANCE OTHERWISE	UNLESS SPECIFIED	TITLE		COMPO.	NENTS COR	PORA	HON
	1		$] \rightarrow $	1 PL +/-	0	''''	MIN	IATURE COL	D CATHODE		
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0		FLUORESCENT LAMP					
			DRAWN BY L. WENGSTROM	APPV'D BY J.K.	DATE 8/9/04	SIZE	55335		3380-24B		
250	RELEASED	8/9/04	- CAD D	RAWING	_	SCALE		RELEASED	REVISION	REV.	SHEET
REV NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED				NONE	DATE 8/9/04	DATE	NO.	1 of 1