

## C535A-WJS/WJN: 5-mm Round White LEDs



### PRODUCT DESCRIPTION

Round LEDs offer superior light output for excellent readability in sunlight and dependable performance. They provide extremely stable light output over long periods of time.

These lamps are made with an advanced optical grade epoxy offering superior high temperature and high moisture resistance performance in lighting and illumination applications.

### FEATURES

- Size (mm): 5
- Color Temperatures:  
Cool White :  
Min . (4600K) / Typical (9000K)
- Luminous Intensity (mcd)  
C535A-WJS/WJN:(1100-4180)
- Viewing angles:  
110°: C535A-WJS/WJN
- Lead - Free
- RoHS Compliant

### APPLICATIONS

- Garden Light
- Channel Letter
- Retail Display Lighting

### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

Items	Symbol	Absolute Maximum Rating	Unit
Forward Current	$I_F$	25	mA
Peak Forward Current <small>Note 1</small>	$I_{FP}$	100	mA
Reverse Voltage	$V_R$	5	V
Power Dissipation	$P_D$	100	mW
Operation Temperature	$T_{opr}$	-40 ~ +95	°C
Storage Temperature	$T_{stg}$	-40 ~ +100	°C
Lead Soldering Temperature	$T_{sol}$	Max. 260°C for 3 sec. max. (3 mm from the base of the epoxy bulb)	

Note:

1. Pulse width  $\leq 0.1$  msec, duty  $\leq 1/10$ .

### TYPICAL ELECTRICAL & OPTICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ )

Characteristics	Color	Symbol	Condition	Unit	Minimum	Typical	Maximum
Forward Voltage	WJS/WJN	$V_F$	$I_F = 20$ mA	V		3.2	4.0
Reverse Current	WJS/WJN	$I_R$	$V_R = 5$ V	μA			100
Luminous Intensity	WJS/WJN	$I_V$	$I_F = 20$ mA	mcd	1100	2750	
Chromaticity Coordinates	WJS/WJN	x	$I_F = 20$ mA			0.2895	
		y	$I_F = 20$ mA			0.2905	
50% Power Angle	WJS/WJN	20½	$I_F = 20$ mA	deg		110	

\* Continuous reverse voltage can cause LED damage.

## INTENSITY BIN LIMIT

Cool White (20 mA) - C535A-WJS/WJN		
Bin Code	Min.(mcd)	Max.(mcd)
T0	1100	1520
U0	1520	2130
V0	2130	3000
W0	3000	4180

\* Tolerance of measurement of luminous intensity is  $\pm 15\%$

## VOLTAGE BIN LIMIT

Cool White (20 mA) - C535A-WJS/WJN		
Bin Code	Min. (V)	Max. (V)
27	2.8	3.0
28	3.0	3.2
29	3.2	3.4
2a	3.4	3.6
2b	3.6	3.8
2c	3.8	4.0

\* Tolerance of measurement of voltage is  $\pm 0.05\text{V}$








## COLOR BIN LIMIT

### Cool White (20 mA) - C535A-WJS/WJN

Bin Code	Sub-bin	x	y
W5	Wv1	0.3455	0.3725
		0.3533	0.3788
		0.3523	0.3698
		0.3449	0.3630
	Wv2	0.3449	0.3630
		0.3523	0.3698
		0.3514	0.3608
		0.3443	0.3535
	Wv3	0.3533	0.3788
		0.3610	0.3850
		0.3598	0.3765
		0.3523	0.3698
	Wv4	0.3523	0.3698
		0.3598	0.3765
		0.3585	0.3680
		0.3514	0.3608
	Ww1	0.3443	0.3535
		0.3514	0.3608
		0.3505	0.3518
		0.3437	0.3440
	Ww2	0.3437	0.3440
		0.3505	0.3518
		0.3495	0.3428
		0.3430	0.3345
	Ww3	0.3514	0.3608
		0.3585	0.3680
		0.3573	0.3595
		0.3505	0.3518
	Ww4	0.3505	0.3518
		0.3573	0.3595
		0.3560	0.3510
		0.3495	0.3428

\* Tolerance of measurement of the color coordinates is  $\pm 0.01$

**CIE CHROMATICITY DIAGRAM**

**ORDER CODE TABLE**

Color	Viewing Angle	Kit Number	Luminous Intensity (mcd)		Color Bin Code	Package	Standoff
			Min.	Max.			
Cool White	110°	C535A-WJS-CT0W0151	1100	4180	W1,W2,W3,W4,W5	Bulk	Yes
		C535A-WJS-CT0W0231	1100	4180	W2,W3	Bulk	Yes
		C535A-WJS-CU0W0231	1520	4180	W2,W3	Bulk	Yes
		C535A-WJS-CV0W0231	2130	4180	W2,W3	Bulk	Yes
		C535A-WJS-CT0W0152	1100	4180	W1,W2,W3,W4,W5	Ammo	Yes
		C535A-WJS-CT0W0232	1100	4180	W2,W3	Ammo	Yes
		C535A-WJS-CU0W0232	1520	4180	W2,W3	Ammo	Yes
		C535A-WJS-CV0W0232	2130	4180	W2,W3	Ammo	Yes
		C535A-WJN-CT0W0151	1100	4180	W1,W2,W3,W4,W5	Bulk	No
		C535A-WJN-CT0W0231	1100	4180	W2,W3	Bulk	No
		C535A-WJN-CU0W0231	1520	4180	W2,W3	Bulk	No
		C535A-WJN-CV0W0231	2130	4180	W2,W3	Bulk	No
		C535A-WJN-CT0W0152	1100	4180	W1,W2,W3,W4,W5	Ammo	No
		C535A-WJN-CT0W0232	1100	4180	W2,W3	Ammo	No
		C535A-WJN-CU0W0232	1520	4180	W2,W3	Ammo	No
		C535A-WJN-CV0W0232	2130	4180	W2,W3	Ammo	No

**Notes:**

- The above kit numbers represent order codes that include multiple intensity-bin and color-bin codes. Only one intensity-bin code and one color-bin code will be shipped on each bulk. Single intensity-bin code and single color-bin codes will not be orderable.
- Please refer to the [HB LED Lamp Reliability Test Standards](#) document for reliability test conditions.
- Please refer to the [HB LED Lamp Soldering & Handling](#) document for information about how to use this LED product safely.

## GRAPHS

The data below are collected from statistical figures that do not necessarily correspond to the actual parameters of each single LED. Hence, these data will be changed without further notice.




FIG.1 FORWARD CURRENT VS.  
FORWARD VOLTAGE.




FIG.2 RELATIVE LUMINOUS INTENSITY VS.  
FORWARD CURRENT




FIG.3 REVERSE CURRENT  
VS. REVERSE VOLTAGE.




FIG.4 RELATIVE LUMINOUS INTENSITY VS.  
WAVELENGTH.  
50% Power Angle : 10°  
(RELATIVE LUMINOUS INTENSITY)




FIG.5 MAXIMUM FORWARD DC CURRENT  
VS AMBIENT TEMPERATURE ( $T_{jmax}=105^{\circ}\text{C}$ )




FIG.6 FAR FIELD PATTERN


## MECHANICAL DIMENSIONS

All dimensions are in mm. Tolerance is  $\pm 0.25$  mm unless otherwise noted.


An epoxy meniscus may extend about 1.5 mm down the leads.

Burr around bottom of epoxy may be 0.5 mm max.

**C535A-WJS:**



**C535A-WJN:**



## NOTES

### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree LED representative or from the [Product Ecology](#) section of the Cree LED website.


### Vision Advisory

**WARNING:** Do not look at an exposed lamp in operation. Eye injury can result.

## KIT NUMBER SYSTEM

Cree LED lamps are tested and sorted into performance bins. A bin is specified by ranges of color, forward voltage, and brightness. Sorted LEDs are packaged for shipping in various convenient options.

Cree LEDs are sold by order codes in combinations of bins called kits. Order codes are configured in the following manner:




## SOLDERING GUIDELINES

The LED soldering specification is shown below(suitable for both leaded solder & lead-free solder):

Manual Soldering		Solder Dipping	
Soldering iron	35 W max	Preheat	110 °C max
Temperature	300 °C max	Preheat time	60 seconds max
		Solder-bath temperature	260 °C Max
Soldering time	3 seconds max	Dipping time	5 seconds max
Position	Not less than 3 mm from the base of the package.	Position	Not less than 3 mm from the base of the package.

- Manual soldering onto the PCB is not recommended because soldering time is uncontrollable.
- The recommended wave soldering is as below:




- Do not apply any stress to the LED package, particularly when heated.
- Only bottom preheat is suggested & should not preheat on top in order to reduce thermal stress experienced by the LEDs.
- The LEDs must not be re used once they have been extracted from PCB.
- After soldering the LEDs, the package should be protected from mechanical shock or vibration until the LEDs have reached 40 °C or below.
- Precautions must be taken as mechanical stress on the LEDs may be caused by PCB warpage or from the clinching and cutting of the LED leads.
- When it is necessary to clam the LEDs during soldering, it is important to ensure no mechanical stress is exerted on the LEDs.
- Cut the LED lead at normal room temperature. Lead cutting at high temperature may cause failure of the LEDs.
- Please refer to the [HB LED Lamp Soldering & Handling](#) document for information about how to use this LED product safely.

## PACKAGING

- The LEDs are packed in cardboard boxes after packaging in normal or anti-electrostatic bags.
- Cardboard boxes will be used to protect the LEDs from mechanical shock during transportation.
- The boxes are not water resistant, and they must be kept away from water and moisture.
- Max 500 pcs per bulk and Max 2500 pcs per ammo.

**Bulk Pack Packaging Type:**



**Ammo Pack Packaging Type:**

