

HB10D

LED High Bay



Features

Housing

Die-formed Cold-rolled Steel and V Hook & Hanging Chain Included
Eco-frame & full Body Linear Construction

Optical

High Transmission Acrylic Shade

Electrical

UL2459 / CSA182.3 Power Connector Included

Lamp

Integrate LED Module with High Lumen Efficiency and High CRI
Rated 50,000 Hours LED Life

Certification

ETL/cETL Listed, Suitable for Damp Locations, **DLC Premium Listed**

Warranty

5 Years Limited Warranty on Driver and LED

Options

- LS with Lens
- EM with Built-in Emergency Driver or External Emergency Driver
- Bi Bi-Level Dimming



DLC Premium Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)	DLC Premium
HB10D-85W-VHO-4000K	120V ~ 277V	81W	4000K	80	11260	43.0" x 9.0" x 3.5"	Premium
HB10D-85W-VHO-5000K	120V ~ 277V	81W	5000K	80	11390	43.0" x 9.0" x 3.5"	Premium
HB10D-105W-VHO-4000K	120V ~ 277V	104W	4000K	80	14550	43.0" x 9.0" x 3.5"	Premium
HB10D-105W-VHO-5000K	120V ~ 277V	104W	5000K	80	14770	43.0" x 9.0" x 3.5"	Premium