


Rev. 1909

LDP-VRM 025-100 CA

Laser Diode Driver



• Output current: 0 .. 2.5 A

• High speed

Adaptive DC/DC converter



Technical Data*

Output current

Max. compliance voltage

Current noise
Current overshoot
Analog modulation

Current settling time

(full scale)

O .. 2.5 A
Single laser diode
up to 100 V
< 3 %
< 5 %
120 kHz typical
100 kHz guaranteed

(full-scale)
Current setting input
Current monitor

0 .. 5 V
0.165 V/A


Trigger Analog / TTL (jumper)

Supply voltage 24 V

Power dissipation
Dimensions in mm
Weight
Operating temperature

TBD 145 x 40 x 25 200 g 0 to +55 °C

* Specifications measured with a fast recovery diode instead of a laser diode. Technical data is preliminary and subject to change without further notice.



Product Description

The LDP-VRM 025-12 CA is a fast driver for typical laser diodes. With its high output voltage it is suitable for IR, blue Ld's and all kinds of LEDs. The internal DC/DC converter stabilizes the voltage drop across the driving MOSFET to prevent excessive losses.

- Innovative current regulation concept actively prevents laser diode from overshoots and over-current
- Protection against transients through regulated current rise time
- Adaptive DC/DC converter for lowest losses

Optional Accessories: None

PicoLAS GmbH Burgstr. 2 52146 Würselen Germany