

# Lux Series G5 CXM-9 COB Arrays White LED





## Features:

#### • High lumen output and efficacy typical

- Over 1825lm, 152 LPW @ 3000K, 90CRI, T<sub>i</sub> = 85°C
- CCT range 2400K, 2700K, 3000K, 3500K, 4000K, 5000K and 6500K
- 3 SDCM and 2 SDCM color binning standard
- Excellent optical emission uniformity and color over angle consistency
- Superior thermal conductivity for uniform heat spreading



# **Applications**

- Spotlights/Track Lights
- Downlights
- Shop Lighting
- Hospitality Lighting

- Architectural and Specialty
- Street Lighting
- Parking Lot and Area Lighting
- Tunnel Lighting

# Contents

Part Number Nomenclature 2
CCT, CRI & R9 Specification2
Chromaticity Bin Structure .3
Ordering Part Numbers4
Operating Characteristics8
Optical and Electrical Charac- eristics
Гуріcal Spectrum 10
Radiation Pattern 10
Mechanical Dimension 11
Shipping Container 11
abel Information 12
Technology Review 13
Test Specifications 13
Handling Notes 14



# **Part Number Nomenclature**

All Luminus COB products are packaged and labeled with part numbers as outlined in the table on page 4. Luminus may include any smaller chromaticity bin that is contained in the larger bin as part of the ordered part. When shipped, each package will contain only a single flux and chromaticity bin. The part number designation is as follows:

CLM	- 9 -	– NN –	– XX –	– VV –	- QQPP -	— FG -	— W
Product Family	LES <sup>1</sup>	CCT <sup>2</sup>	Min. CRI <sup>3</sup>	Typical Voltage	Package Configurator <sup>4</sup>	Flux Bin	Chromaticity Bin
Chip on Board, Multi-die	9mm LES diameter	See Note 2 below	CRI See Table Below	Volts (V)	TC/A50 TC/A52	Lumens	See page 3 for bins

Notes:

- 1. Light Emitting Surface (LES) Diameter.
- 2. Correlated Color Temperature (CCT), NN nomenclature corresponds to the following:

24 = 2400K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K 65 = 6500K

- 3. Minimum Color Rendering Index (CRI).
- 4. TC is a standard substrate with sulfur resistance process, TA is an alternative substrate; 5 means Lux G5 COB products. 0 means a product with chromaticity on the BBL; 2 means a product with chromaticity below the BBL which is also known as Sensus chromaticity. Sensus chromaticity offers increased color gamut to make whites crisper and to render more vivid and saturated colors.
- 5. Luminus part numbers may be accompanied by prefixes or suffixes. The most common is the "Rev01" suffix indicating a part is fully released and carries a full warranty. These additional characters may appear on shipping labels, packing slips and invoices. In all cases the basic part number described above will always be included.

## CCT, CRI and R9 Values

Correlated Color Temperatures	XX Value	CRI	*R9
2400K, 2700K, 3000K, 3500K, 4000K, 5000K, 6500K	90	>90	>50
2700K, 3000K	05	. 05	>85
3500K, 4000K, 5000K	95	>95	>75

Note: R9 values have a tolerance of +/- 5%

2



# **Chromaticity Bin Structure**

Chromaticity Bins: 1931 CIE Color Space



The following tables describe the chromaticity bin center points, the orientation angle for the MacAdam ellipse ( $\theta$ °), and the maximum radii for the ellipses. The ANSI Bin is provided for reference.

сст	Center Point		Angle	3-step Bin		2-step Bin	
CCT	CIEx	CIEy	θ (°)	а	b	а	b
2400K	0.4810	0.4140	53.7	0.0081	0.0042	0.0054	0.0028
2700K	0.4578	0.4101	53.7	0.0081	0.0042	0.0054	0.0028
3000K	0.4338	0.4030	53.2	0.0083	0.0041	0.0056	0.0027
3500K	0.4073	0.3917	54.0	0.0093	0.0041	0.0062	0.0028
4000K	0.3818	0.3797	53.7	0.0094	0.0040	0.0063	0.0027
5000K	0.3447	0.3553	59.6	0.0082	0.0035	0.0055	0.0023
6500K	0.3123	0.3282	58.6	0.0067	0.0029	0.0045	0.0019

Note: Luminus maintains a +/- 0.005 tolerance on chromaticity (CIEx and CIEy) measurements



# **Ordering Part Numbers - TA50**

The following tables describe products with typical flux and minimum flux measured at 360mA and specified at  $T_j = 85^{\circ}$ C. The values at 25°C are calculated and shown for reference only.

	Output Flux (lm)			Color	Ordering P	art Number
ССТ	Тур. (85°С)	Min. (85°C)	Calculated Typ. (25°C)	Rendering Index (min.)	3-step MacAdam Ellipse	2-step MacAdam Ellipse
2400K	1680	1560	1850	90	CXM-9-24-90-36-TA50-F6-3	CXM-9-24-90-36-TA50-F6-2
27001/	1795	1670	1975	90	CXM-9-27-90-36-TA50-F6-3	CXM-9-27-90-36-TA50-F6-2
2700K	1640	1525	1800	95	CXM-9-27-95-36-TA50-F6-3	CXM-9-27-95-36-TA50-F6-2
20001/	1825	1700	2010	90	CXM-9-30-90-36-TA50-F6-3	CXM-9-30-90-36-TA50-F6-2
3000K	1695	1575	1865	95	CXM-9-30-95-36-TA50-F6-3	CXM-9-30-95-36-TA50-F6-2
25001/	1910	1775	2100	90	CXM-9-35-90-36-TA50-F6-3	CXM-9-35-90-36-TA50-F6-2
3500K	1705	1585	1875	95	CXM-9-35-95-36-TA50-F6-3	CXM-9-35-95-36-TA50-F6-2
40001/	1910	1775	2100	90	CXM-9-40-90-36-TA50-F6-3	CXM-9-40-90-36-TA50-F6-2
4000K	1775	1650	1950	95	CXM-9-40-95-36-TA50-F6-3	CXM-9-40-95-36-TA50-F6-2
50001/	1890	1760	2080	90	CXM-9-50-90-36-TA50-F6-3	CXM-9-50-90-36-TA50-F6-2
5000K	1790	1665	1970	95	CXM-9-50-95-36-TA50-F6-3	CXM-9-50-95-36-TA50-F6-2
6500K	1860	1730	2045	90	CXM-9-65-90-36-TA50-F6-3	CXM-9-65-90-36-TA50-F6-2

Note: Luminus maintains a +/- 6% tolerance on flux measurements. Luminus maintains a +/- 2% tolerance on CRI measurements.



# Ordering Part Numbers - TC50

The following tables describe products with typical flux and minimum flux measured at 360mA and specified at  $T_j = 85^{\circ}$ C. The values at 25°C are calculated and shown for reference only.

	Output Flux (lm)			Color	Ordering P	art Number
сст	Typ. (85°C)	Min. (85°C)	Calculated Typ. (25°C)	Rendering Index (min.)	3-step MacAdam Ellipse	2-step MacAdam Ellipse
2400K	1680	1560	1850	90	CXM-9-24-90-36-TC50-F6-3	CXM-9-24-90-36-TC50-F6-2
27001/	1795	1670	1975	90	CXM-9-27-90-36-TC50-F6-3	CXM-9-27-90-36-TC50-F6-2
2700K	1640	1525	1800	95	CXM-9-27-95-36-TC50-F6-3	CXM-9-27-95-36-TC50-F6-2
2000//	1825	1700	2010	90	CXM-9-30-90-36-TC50-F6-3	CXM-9-30-90-36-TC50-F6-2
3000K	1695	1575	1865	95	CXM-9-30-95-36-TC50-F6-3	CXM-9-30-95-36-TC50-F6-2
25001/	1910	1775	2100	90	CXM-9-35-90-36-TC50-F6-3	CXM-9-35-90-36-TC50-F6-2
3500K	1705	1585	1875	95	CXM-9-35-95-36-TC50-F6-3	CXM-9-35-95-36-TC50-F6-2
40001/	1910	1775	2100	90	CXM-9-40-90-36-TC50-F6-3	CXM-9-40-90-36-TC50-F6-2
4000K	1775	1650	1950	95	CXM-9-40-95-36-TC50-F6-3	CXM-9-40-95-36-TC50-F6-2
50001/	1890	1760	2080	90	CXM-9-50-90-36-TC50-F6-3	CXM-9-50-90-36-TC50-F6-2
5000K	1790	1665	1970	95	CXM-9-50-95-36-TC50-F6-3	CXM-9-50-95-36-TC50-F6-2
6500K	1860	1730	2045	90	CXM-9-65-90-36-TC50-F6-3	CXM-9-65-90-36-TC50-F6-2

Note: Luminus maintains a +/- 6% tolerance on flux measurements. Luminus maintains a +/- 2% tolerance on CRI measurements.



## **Chromaticity Bin Structure**

Chromaticity Bins: 1931 CIE Color Space



The following tables describe the chromaticity bin center points, the orientation angle for the MacAdam ellipse ( $\theta$ °), and the maximum radii for the ellipses. The ANSI Bin is provided for reference.

ССТ	Center Point		Angle	3-step Bin		2-step Bin	
	CIEx	CIEy	θ (°)	а	b	а	b
2700K	0.4505	0.3965	53.7	0.0081	0.0042	0.0054	0.0028
3000K	0.4252	0.3877	53.6	0.0083	0.0041	0.0056	0.0027
3500K	0.4067	0.3845	54.0	0.0093	0.0041	0.0061	0.0028

Note: Luminus maintains a +/- 0.005 tolerance on chromaticity (CIEx and CIEy) measurements



# Ordering Part Numbers - TC/TA52 Sensus (BBBL)

The following tables describe products with typical flux and minimum flux measured at 360mA and specified at  $T_j = 85^{\circ}$ C. The values at 25°C are calculated and shown for reference only.

	Output Flux (lm)			Color	Ordering P	art Number		
ССТ	Тур. (85°С)	Min. (85°C)	Calculated Typ. (25°C)	Rendering Index (min.)	3-step MacAdam Ellipse	2-step MacAdam Ellipse		
27001/	1705	1615	1010	00	CXM-9-27-90-36-TC52-F6-3	CXM-9-27-90-36-TC52-F6-2		
2700K 1735	1/35	5 1015	1910	90	CXM-9-27-90-36-TA52-F6-3	CXM-9-27-90-36-TA52-F6-2		
2000/	1770	1650	1950	1050	1050		CXM-9-30-90-36-TC52-F6-3	CXM-9-30-90-36-TC52-F6-2
3000K 1770	1770	1650		90	CXM-9-30-90-36-TA52-F6-3	CXM-9-30-90-36-TA52-F6-2		
25001/	1015	1815 1690	2000	90	CXM-9-35-90-36-TC52-F6-3	CXM-9-35-90-36-TC52-F6-2		
3500K	1815				CXM-9-35-90-36-TA52-F6-3	CXM-9-35-90-36-TA52-F6-2		

Note: Luminus maintains a +/- 6% tolerance on flux measurements. Luminus maintains a +/- 2% tolerance on CRI measurements.



Parameter	Symbol	Minimum	Typical	Maximum	Unit
Forward Current <sup>2</sup>	l <sub>f</sub>		360	750	mA
Forward Voltage <sup>3</sup>	V <sub>f</sub>	31.5	33.2	35.5	V
Power			12	26.5	W
Operating Case Temperature	T <sub>c</sub>			105	°C
Light Emitting Surface Diameter <sup>4</sup>	LES		9.8		mm
Thermal Resistance (junction-to-case)	$\Theta_{jc}$		0.32		°C/W
Junction Temperature	Tj			140	°C
Viewing Angle			120		Degree

Notes:

1. Device measurements are at  $Tj = 85^{\circ}C$ .

2. To prevent damage refer to operating conditions and derating curves for appropriate maximum operating conditions

3. Voltage is rated at typical forward current. For voltage at higher drive current, refer to performance graphs.

4. Luminus designed a complex, unique phosphor ring. The LES diameter is defined consistent with industry practices and aligned to optical characteristics. The LES diameter is not measured at the surface of the phosphor layer. Please use ray files for all optics designs.

5. Device operation not recommended at drive currents less than 10% of the typical value

6. Caution must be taken not to stare at the light emitted from these LEDs. Under special circumstances, the high intensity could damage the eye.

7. All product operating specifications are subject to change without advance notice.



# **Optical & Electrical Characteristics**



#### **Relative Output Flux vs. Junction Temperature**



Change in CIE\_x/y vs. Junction Temp. (3000K, 90CRI)





#### **Change in Voltage vs. Junction Temperature**



#### Change in CIE\_x/y vs. Forward Current (3000K, 90CRI)



Forward Current vs. Forward Voltage @ 85°C



# **Typical Spectrum**



**Radiation Pattern** 

#### **Typical Polar Radiation Pattern**

## Typical Angular Radiation Pattern





# **Derating Curves**



**-** 10



# **Mechanical Dimensions - TA50**

0.87±0.15 [.034±.006]

(1.37 [.054])

Note: Unless otherwise specified, tolerance is  $\pm 0.3$ mm





# **Shipping Container - TA50**



Note: 60 pcs per tray and 5 trays are stacked together to be sealed in an anti-static bag.





Note: The anti-static bag is boxed for easier storage, 300pcs per box.





## **Mechanical Dimensions - TC50**



## **Shipping Container - TC50**



Note: 80 pcs per tray and 5 trays are stacked together to be sealed in an anti-static bag.



Note: The anti-static bag is boxed for easier storage, 400pcs per box.



Label model -- for illustration only

## Notes:

**Label Information** 

- (1) Manufacturer part number, flux bin and chromaticity bin
- (2) Customer part number
- (3) Rev.01 indicates a fully released product
- (4) Box ID
- 5 Production ID
- (6) Total number of units in a box



# **Technology Overview**

Luminus Chip-on-Board (COB) LED series have consistently delivered the highest lumen performance with the best color quality of any COB supplier. Driving performance enhancements through more than 5 generations of COB products has provided Luminus a comprehensive understanding of the lighting market for directional sources positioning Luminus as the COB manufacturer of choice for the most discriminating lighting manufacturers.

#### Reliability

Designed from the ground up, the Luminus COB LED is one of the most reliable light sources in the world today.

#### **UL and IEC Recognized Compliance**

Luminus COB arrays are tested in accordance with ANSI/UL 8750 to ensure safe operation for their intended applications. Further, Luminus maintains IEC-62031 safety ratings on all COB products.

#### **REACH & RoHS Compliance**

All LED products manufactured by Luminus are REACH and RoHS compliant and free of hazardous materials, including lead and mercury.

## **Test Specifications**

Every Luminus LED is fully tested to ensure it meets the high quality standards customers have come to expect from Luminus' products.

#### **Traceability**

Each Luminus COB LED is marked with a 2D bar code that contains a unique serial number. With this serial number, Luminus has the ability to provide customers with actual test data measurements for a specific LED. In addition, the 2D bar code is linked to manufacturing date codes that enables traceability of production processes and materials.

#### **Testing Temperature**

Luminus COB products are measured at temperatures typical for the LED operating in the fixture. Each device is tested at 85°C junction temperature eliminating the need to scale data sheet specifications to real world situations.

#### **Chromaticity Bin Range**

Chromaticity binning delivers color consistency for every order. Standard products are delivered with a 3-step MacAdam ellipse. This ensures color performance matching in the application. For the most demanding application, Luminus is one of only a few companies that can provide a 2 SDCM bin distribution. These tightly controlled, small distribution bins provide customers predictable, repeatable colors.



# **Handling Notes**

Luminus products are designed for robust performance in general lighting application. However, care must be taken when handling and assembling the LEDs into their fixtures. To avoid damaging Luminus COBs please follow these guidelines.

The following is an overview of the application notes detailing some of the practices to follow when working with these devices. More detailed information is available on the Luminus web site at www.luminus.com.

#### **General Handling**

Devices are made to be lifted or carried with tweezers on two adjacent corners opposite the contact pads. At no time should the devices be handled by or should anything come in contact with the light emitting surface (LES) area. This area includes the yellow colored circular area and the ring surrounding it. There are electrical connections under the LES which if damaged will cause the device to fail. In addition, the ring frame itself should not be used for moving, lifting or carrying the device. Also do not attach any optics or mechanical holders to the ring as it is not capable to handle the mechanical stress.

#### **Storage Condition**

#### Please follow the conditions below.

Before opened	Temperature 5~30°C, relative humidity less than 60%.
After opened	Temperature 5~30°C, relative humidity less than 60%. After opening, LED should be kept in an aluminum moisture proof bag with a moisture absorbent material
Avoid Corrosive gas	Avoid exposing to air with corrosive gas. If exposed, electrode surface would be damaged, which may affect soldering. More detailed information is available on the Luminus Applications Resources web pages.

## **Static Electricity**

Luminus COBs are electronic devices which can be damaged by electrostatic discharge (ESD). Please use appropriate measures to assure the devices do not experience ESD during their handling and or storage. ESD protection guidelines should be used at all time when working with Luminus COBs.

Storage	Luminus products are delivered in ESD shielded bags and should be stored in these bags until used
Transporting	When transporting the devices from one assembly area to another, ESD shielded carts and carriers should be used
Assembly	Individuals handling Luminus COBs during assembly should be trained in ESD protection practices. Assemblers should maintain constant conductive contact with a path to ground by means of a wrist strap, ankle straps, mat or other ESD protection system



## **Chemical Compatibility**

The resin material used to form the LES can getter hydrocarbons from the surrounding environment. As a result, certain chemical compounds (H<sub>2</sub>SO<sub>4</sub>, H<sub>2</sub>S, SO<sub>2</sub>, NH<sub>3</sub>, H<sub>3</sub>PO<sub>4</sub>, etc.) are not recommended for use with the Luminus products. Use of these compounds can cause damage to the light output of the device and may permanently damage the device. Please refer to the table below for a list of the compounds not recommended for use with the Luminus COB products.

Common Chemicals Know to Adversely Affect Luminus Devices						
Acetates	Ethers	Potassium hydroxide				
Acetic acid	Cl, F or Br containing compounds	Siloxanes				
Acrylates	Liquid hydrocarbons	Sodium Hydroxide				
Aldehydes	Hydrochloric Acid	Sulfur compounds				
Aldehydes	Ketones	Sulfuric Acid				
Amines	Nitric Acid	Toluene				
Benzene	Phosphoric acid	Xylenes				
Dienes						

## Thermal Interface Material (TIM)

Proper thermal management is critical for successful operation of any LED system. Excess operating temperature can reduce the light output of the device. Excessive heating can cause permanent damage to the device. Proper TIM material is a crucial component for effective heat transfer away from the LED during normal operation. Please refer to www.luminus.com for specific recommendations for TIM solutions.

Please refer to https://www.luminus.com/resource/application-notes for more application note information.