

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
2	5.0	.021	.034	0.43	10,000	C-2R
6803	5.0	.060	.030	0.38	100,000	C-2R
6833	5.0	.060	.050	0.63	100,000	C-2R
7133	5.0	.075	.090	1.13	25,000	C-2R
7153	5.0	.115	.150	1.89	40,000	C-2R
. BW79	6.0	.065	.110	1.40	10,000	C-2R

NOTES:

- 1. GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS CONSTRUCTION TO PROVIDE UNDISTORTED END VIEWING.
- 2. WIRE TERMINALS TO BE TINNED DUMET TYPE WIRE. OPTIONAL PLATING MATERIALS ARE AVAILABLE.
- 3. ALL LAMPS TO BE 100% AGED FOR AN EQUIVALENT OF TEN HOURS OF THE RATED VOLTAGES.
- 4. FINAL INSPECTION ON ALL LAMPS TO BE PER MIL. STD. 105D TO AN AQL OF 2.5. NOTE: AS15 TYPE LAMPS WILL BE 100% INSPECTED FOR AMPERAGE AND MSCP RATINGS.
- 5. ALL DIMENSIONS PROVIDED HEREIN, NOT LISTING TOLERANCES, ARE CONSIDERED REFERENCE DIMENSIONS ONLY.

			METRIC		IONS ARE IMETERS		IKI	[MDO	TENTS CODI	DOD AT	TON
			TOLERANCE UNLESS OTHERWISE SPECIFIED		COMPONENTS CORPORATION							
		1		1 PL +	-/- 0.2	TITLE						
С	LEAD DIA. CHNG TO Ø0.2 REF.	02/08/00	THIRD ANGLE	2 PL +			T-3/4 S	STAND	ARD W	IRE TERMINA	L LAMF	'
В	CORRECTION ON REV. LAMP LIST	01/28/00		ANGLE +/- 0								
Α	DRAWING CONVERTED TO CAD-LAMPS 7100,	01/17/00	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.					
	8534, BW23,6153, 8666, 7102 DELETED		L. WENGSTROM	BW	02/08/00	Α	55335	NO.	WIRE	ETERMINAL	. T-3/4	
	RELEASED	12/84	- CAD DRAWING -		SCALE		RELEASED		REVISION	REV.	SHEET	
REV NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED			00,122			12/84	DATE 02/08/00	NO. C	1 _{OF} 1