SIEMENS

Data sheet US2:HFC222NR



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: CSA V. Rating: 240V A. Rating: 60A Wattage: 3W No. Of Poles: 2P F. Rating: 60Hz Action: SINGLE THROW Material: 304SS Enclosure: TYPE 3R. 2-3 point mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: OUTDOOR

Figure similar

General technical data		
mechanical service life (operating cycles) typical	10000	
fastening method	SURFACE	
number of poles	2	
suitability for operation	DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS	
Electricity		
ampacity	60 A	
supply voltage frequency rated value 50/60 Hz	Yes	
Environmental conditions		
ambient temperature during operation maximum	85 °C	
ambient temperature during operation minimum	-29 °C	
Model		
product brand name	SIEMENS	
product sub brand name	VBII	
product type designation	HEAVY DUTY SWITCH	
type of electrical connection	MECHANICAL LUGS	
Mechanical Design		
design of the housing	TYPE 3R	
design of the actuating element	SINGLE THROW	
material	STEEL	
General product approval		
certificate of suitability	UL98 / CSA	

last modified:	9/15/2021
----------------	-----------