



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: CSA V. Rating: 600V A. Rating: 100A Wattage: 4W No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material: STEEL Enclosure: TYPE 1. 2-3 point mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDOOR

General technical data

mechanical service life (operating cycles) typical	10000
fastening method	SURFACE
number of poles	3
suitability for operation	DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS

Electricity

ampacity	100 A
supply voltage frequency rated value 50/60 Hz	Yes

Environmental conditions

ambient temperature during operation maximum	85 °C
ambient temperature during operation minimum	-29 °C

Model

product brand name	SIEMENS
product sub brand name	VBII
product type designation	HEAVY DUTY SWITCH
type of electrical connection	MECHANICAL LUGS

Mechanical Design

design of the housing	TYPE 1
design of the actuating element	SINGLE THROW
material	STEEL

General product approval

certificate of suitability	UL98 / CSA
----------------------------	------------

last modified:

9/15/2021 

