

	LTR	DATE	REVISION	CHK	APD
	K	10/25/02	82332C- REVISED & REDRAWN ON NEW FORMAT JMB		
	L	03/07/07	85292B-CHG 692227 TO 692469 PJM		
-					
-					
-					
-					

	914-796	LABEL	6.700	EAD
	580509	CARTON	6.700	EAD
	580278	PARTITION	20.100	EAD
	580219	FOAM	6.700	EAD
11	901-104	O-RING	1000	EA
10	899-045	RESISTOR	1000	EΑ
9	903-067	NUT	1000	EA
8	284000-4	KNOB	1000	EA
7	087232	ADHESIVE	. 27	LB
6	281002-4	ORIENTATION DISC	1000	EA
5	915-008	LAMP	1000	EA
4	692469	SOLDER (TIN DIP)	. 20	LB
3	281002-3	TERMINAL	2000	ΕA
2	425502	INK	. 0 1 6	FOZ
1	284000-1	BODY	1000	ΕA
NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

## BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

0	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS,-MINIMUM CPK VALUE
(ST)	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS

SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. MATL SPEC

	COP	IES	ΤO							
ĺ	1	9	18							
	2	10	19	FINISH						
	3	12	20							
	4	13	2 1	DRW	JMB	DATE	10/25/02	SCALE	2 = 1	
	5	14	23	CHK		DATE		SUPER DR		
	6	15	33	CLIK		DAIL		SUPER DR		
	7	16	43	APPD		DATE		RAW STK WT		
	8	17	53							LBS/
	TOLERANCE UNLESS OTHERWISE SPECIFIED									
- 1	TWO		$\wedge \cap \vdash$		Λ 1			EDVCTION	1	


TWO PLACE DEC ±.01 FRACTION ± THREE PLACE DEC ±.005 ANGULAR ±1°

TITLE INDICATING MICRO-FUSE HOLDER 32V. WITH STRAIGHT TERMINALS



1. PLACE ASSEMBLED FUSEHOLDERS (150 PIECES MAX) INTO CARTON 580509 LINED WITH BAG 890-620, CLOSE & SEAL WITH TAPE 088120. AFFIX LABEL

914-796 PRINTED TO GENERAL LABEL SPECIFICATION LS-000003. FOR SMALLER QUANTITIES, USE THE SAME PACKING MATERIALS AND ADD BROWN PAPER TO FILL THE EMPTY SPACE IN THE CARTON.



02800004Z