PD-9501GCI/DC

Single-Port, IEEE 802.3bt Type3 60W, 20-60 VDC, Industrial PoE Midspan

Summary

The Microchip PD-9501GCI is a single-port, high-power solution for remote powering of current and emerging high-power indoor applications. Generating 60W, the 9501GCI enables remote power for a new range of applications including wireless access points, Pan-Tilt Zoom (PTZ) cameras and other IP terminals. It complies to IEEE 802.3at PoE standard and is backward compatible to IEEE 802.3af. It can power both existing 10/100/1000Base-T network devices and 1000Base-T devices such as wireless IEEE wireless access points.



Key Features

- IEEE 802.3BT type 3 compliant
- IEEE 802.3af/at backward compatible
- Dual DC inputs 20–60 VDC range
- Industrial rated IP30
- Extended temp range:
 -40°C to +75°C
- Plug and play installation
- Supports 10/100/1000 Mbps

Specifications

| Feature | Description | |
|-------------------------------------|---|--|
| No. of Ports | 1 | |
| Data Rates | 10/100/1000 Mbps | |
| Power over Ethernet Output | Pin Assignment and Polarity: 1/2 (-), 3/6 (+), 4/5 (+), 7/8 (-) Output Voltage: 55 Vdc | |
| User Port Power | 60 Watts (Guaranteed) | |
| Input Power Requirements | DC Input Voltage: 20 to 60 Vdc DC Input Current: 4A max | |
| Dimensions | 35 mm (W) \times 111 mm (H) \times 78 mm (L) 1.38 in. \times 4.37 in. \times 3.07 in | |
| Weight | 0.82 lbs (373g) | |
| Indicators | Power 1 - Power 1 Source is connected Power 2 - Power 2 Source is connected Alarm - One of Power 1 or Power 2 sources is faulty PoE - PoE is active and delivering power | |
| Connectors | Shielded RJ-45, EIA 568 A and 568 B | |
| Environmental Conditions | Operating Ambient Temperature: -40°F to +167°F (-40°C to +75°C) Storage Temperature: -40°F to +185°F (-40°C to +85°C) | |
| Reliability | MTBF: 170,000 hrs. @25°C | |
| Thermal Rating | 32BTU/Hr @60 Vdc | |
| Warranty | 3 years | |
| Regulatory Compliance | IEEE 802.3at (PoE), RoHS Compliant, WEEE Compliant, CE | |
| Electromagnetic Emission & Immunity | FCC Part 15, Class A EN 55032 Class A (Emissions) EN 55024 (Immunity) | |
| Safety Approvals | UL508 UL/EN/IEC 60950-1 (ed. 2) | |
| Shock | IEC 60068-2-27 | |
| Freefall | IEC 60068-2-31 | |
| Vibration | IEC 60068-2-6 | |



Ordering Information

| Product Name | Description | Part Number |
|---------------|---|---------------|
| PD-9501GCI/DC | Single-Port, IEEE 802.3bt Type3 60W, 20-60 VDC, Industrial PoE Midspan | PD-9501GCI/DC |

For More Information

www.microsemi.com



The Microchip name and logo and the Microchip logo are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. All other trademarks mentioned herein are property of their respective companies.
© 2020, Microchip Technology Incorporated. All Rights Reserved. 2/20

DS00003363A

