

TECHNICAL DATASHEET **ATX 650W** FSP650-50AAA



FSP650-50AAA

Features

- Certified CB 62368-1
- Meet 80 Plus Bronze Efficiency
- Intel Design ATX 12V V1.43
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

SAFETY STANDARD APPROVAL









DESCRIPTION

FSP AAA Series features with eco-friendly design, which allows AAA series to reach up to 85% efficiency. AAA series also equipped with complete protection to prevent your system from damage. AAA series does the job efficiently and reliably, making it a stable power supply unit built to satisfy the demands of all kind of system build.

GENERAL SPECIFICATIONS

Dimension: 140 x 150 x 86 (mm)

 $(L \times W \times H)$ 5.51 x 5.91 x 3.39 (inch)

Meet 80 Plus Bronze Efficiency Efficiency:

Hold-up time: 115V / 60Hz: ≥ 16ms

230V / 50Hz: ≥ 16ms

Operating altitude 2.000 meters above sea level

MTBF: 100,000 hours of continuous

operation at 25°C, Max. output load

Environment

Storage temperature:

0°C to 40°C Working temperature: -40°C to + 70°C

Working humidity: 85% RH non-condensing

Storage humidity: 95% RH non-condensing

INPUT SPECIFICATIONS

Input voltage: 90-264Vac Input frequency: 47-63Hz

Input current: 115Vac @ 9A, 230Vac @ 4.5A



TECHNICAL DATASHEET ATX 650W FSP650-50AAA

OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb
Max	20A	20A	54A	0.3A	2.5A
Min.	0A	0A	0.1A	0A	0A
Regulation	±5%	±5%	±5%	±5%	±5%
Ripple/Noise	50 mV	50 mV	120 mV	120 mV	50 mV

The +3.3V and +5V total output shall not exceed 130W

MECHANICAL SPECIFICATIONS

