



Non-reversing motor starter, Size 1, Three phase full voltage, Solid-state overload relay, OLR amp range 0.75-3.4A, Combination type, 30A non-fusible disconnect, Encl NEMA type 4X 304 S-Steel, Water/dust tight noncorrosive, Extra-wide enclosure

|                                                                          |                                                                      |
|--------------------------------------------------------------------------|----------------------------------------------------------------------|
| product brand name                                                       | Class 17 & 25                                                        |
| design of the product                                                    | Full-voltage non-reversing motor starter with non-fusible disconnect |
| special product feature                                                  | ESP200 overload relay; Dual voltage coil                             |
| <b>General technical data</b>                                            |                                                                      |
| Height x Width x Depth [in]                                              | 24 × 20 × 8 in                                                       |
| touch protection against electrical shock                                | (NA for enclosed products)                                           |
| installation altitude [ft] at height above sea level maximum             | 6560 ft                                                              |
| ambient temperature [°F]                                                 |                                                                      |
| • during storage                                                         | -22 ... +149 °F                                                      |
| • during operation                                                       | -4 ... +104 °F                                                       |
| ambient temperature                                                      |                                                                      |
| • during storage                                                         | -30 ... +65 °C                                                       |
| • during operation                                                       | -20 ... +40 °C                                                       |
| <b>Horsepower ratings</b>                                                |                                                                      |
| yielded mechanical performance [hp] for 3-phase AC motor                 |                                                                      |
| • at 200/208 V rated value                                               | 0.5 hp                                                               |
| • at 220/230 V rated value                                               | 0.75 hp                                                              |
| • at 460/480 V rated value                                               | 1.5 hp                                                               |
| • at 575/600 V rated value                                               | 2 hp                                                                 |
| <b>Contactor</b>                                                         |                                                                      |
| size of contactor                                                        | NEMA controller size 1                                               |
| number of NO contacts for main contacts                                  | 3                                                                    |
| operational current at AC at 600 V rated value                           | 27 A                                                                 |
| mechanical service life (operating cycles) of the main contacts typical  | 10000000                                                             |
| <b>Auxiliary contact</b>                                                 |                                                                      |
| number of NC contacts at contactor for auxiliary contacts                | 0                                                                    |
| number of NO contacts at contactor for auxiliary contacts                | 1                                                                    |
| number of total auxiliary contacts maximum                               | 8                                                                    |
| contact rating of auxiliary contacts of contactor according to UL        | 345VA@115VAC / 768VA@240VAC                                          |
| <b>Coil</b>                                                              |                                                                      |
| type of voltage of the control supply voltage                            | AC                                                                   |
| control supply voltage                                                   |                                                                      |
| • at AC at 60 Hz rated value                                             | 220 ... 480 V                                                        |
| holding power at AC minimum                                              | 8.6 W                                                                |
| apparent pick-up power of magnet coil at AC                              | 218 VA                                                               |
| apparent holding power of magnet coil at AC                              | 25 VA                                                                |
| operating range factor control supply voltage rated value of magnet coil | 0.85 ... 1.1                                                         |
| percentual drop-out voltage of magnet coil related to the input voltage  | 50 %                                                                 |

|                                                                                                                          |                                                |
|--------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| ON-delay time                                                                                                            | 19 ... 29 ms                                   |
| OFF-delay time                                                                                                           | 10 ... 24 ms                                   |
| <b>Overload relay</b>                                                                                                    |                                                |
| product function                                                                                                         |                                                |
| • overload protection                                                                                                    | Yes                                            |
| • phase failure detection                                                                                                | Yes                                            |
| • asymmetry detection                                                                                                    | Yes                                            |
| • ground fault detection                                                                                                 | Yes                                            |
| • test function                                                                                                          | Yes                                            |
| • external reset                                                                                                         | Yes                                            |
| reset function                                                                                                           | Manual, automatic and remote                   |
| trip class                                                                                                               | CLASS 5 / 10 / 20 (factory set) / 30           |
| adjustable current response value current of the current-dependent overload release                                      | 0.75 ... 3.4 A                                 |
| make time with automatic start after power failure maximum                                                               | 3 s                                            |
| relative repeat accuracy                                                                                                 | 1 %                                            |
| product feature protective coating on printed-circuit board                                                              | Yes                                            |
| number of NC contacts of auxiliary contacts of overload relay                                                            | 1                                              |
| number of NO contacts of auxiliary contacts of overload relay                                                            | 1                                              |
| operational current of auxiliary contacts of overload relay                                                              |                                                |
| • at AC at 600 V                                                                                                         | 5 A                                            |
| • at DC at 250 V                                                                                                         | 1 A                                            |
| contact rating of auxiliary contacts of overload relay according to UL                                                   | 5                                              |
| insulation voltage (Ui)                                                                                                  |                                                |
| • with single-phase operation at AC rated value                                                                          | 600 V                                          |
| • with multi-phase operation at AC rated value                                                                           | 300 V                                          |
| <b>Disconnect Switch</b>                                                                                                 |                                                |
| response value of switch disconnecter                                                                                    | 30                                             |
| design of fuse holder                                                                                                    | non-fusible                                    |
| operating class of the fuse link                                                                                         | non-fusible                                    |
| <b>Enclosure</b>                                                                                                         |                                                |
| degree of protection NEMA rating                                                                                         | 4, 304                                         |
| design of the housing                                                                                                    | Extra-wide                                     |
| design of the housing                                                                                                    | dustproof, waterproof & resistant to corrosion |
| <b>Mounting/wiring</b>                                                                                                   |                                                |
| mounting position                                                                                                        | vertical                                       |
| fastening method                                                                                                         | Surface mounting and installation              |
| type of electrical connection for supply voltage line-side                                                               | Box lug                                        |
| tightening torque [lbf-in] for supply                                                                                    | 35 ... 35 lbf-in                               |
| type of connectable conductor cross-sections at line-side for AWG cables single or multi-stranded                        | 1                                              |
| temperature of the conductor for supply maximum permissible                                                              | 75 °C                                          |
| material of the conductor for supply                                                                                     | AL or CU                                       |
| type of electrical connection for load-side outgoing feeder                                                              | Screw-type terminals                           |
| tightening torque [lbf-in] for load-side outgoing feeder                                                                 | 20 ... 24 lbf-in                               |
| type of connectable conductor cross-sections for AWG cables for load-side outgoing feeder single or multi-stranded       | 2                                              |
| temperature of the conductor for load-side outgoing feeder maximum permissible                                           | 75 °C                                          |
| material of the conductor for load-side outgoing feeder                                                                  | CU                                             |
| type of electrical connection of magnet coil                                                                             | Screw-type terminals                           |
| tightening torque [lbf-in] at magnet coil                                                                                | 5 ... 12 lbf-in                                |
| type of connectable conductor cross-sections of magnet coil for AWG cables single or multi-stranded                      | 2                                              |
| temperature of the conductor at magnet coil maximum permissible                                                          | 75 °C                                          |
| material of the conductor at magnet coil                                                                                 | CU                                             |
| type of electrical connection for auxiliary contacts                                                                     | Screw-type terminals                           |
| tightening torque [lbf-in] at contactor for auxiliary contacts                                                           | 10 ... 15 lbf-in                               |
| type of connectable conductor cross-sections at contactor for AWG cables for auxiliary contacts single or multi-stranded | 1                                              |
| temperature of the conductor at contactor for auxiliary contacts                                                         | 75 °C                                          |

|                                                                                                                               |                                     |
|-------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| maximum permissible                                                                                                           |                                     |
| material of the conductor at contactor for auxiliary contacts                                                                 | CU                                  |
| type of electrical connection at overload relay for auxiliary contacts                                                        | Screw-type terminals                |
| tightening torque [lbf-in] at overload relay for auxiliary contacts                                                           | 7 ... 10 lbf-in                     |
| type of connectable conductor cross-sections at overload relay for AWG cables for auxiliary contacts single or multi-stranded | 2                                   |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                     | 75 °C                               |
| material of the conductor at overload relay for auxiliary contacts                                                            | CU                                  |
| <b>Short-circuit current rating</b>                                                                                           |                                     |
| design of the fuse link for short-circuit protection of the main circuit required                                             | 10                                  |
| certificate of suitability                                                                                                    | NEMA ICS 2; UL 508; CSA 22.2, No.14 |
| <b>Further information</b>                                                                                                    |                                     |

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:17DUB82WC>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**


<https://support.industry.siemens.com/cs/US/en/ps/US2:17DUB82WC>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:17DUB82WC&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:17DUB82WC&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:17DUB82WC/certificate>





D68782001

last modified:

12/3/2022