ZCEG1

Limit switch head, Limit switches XC Standard, ZCE, M16 booted nitrile end plunger





Main

Series name Standard format Product or Component Type Device short name Elimit switch head Product Compatibility Product Compatibility XCKP XCKD XCKT XCMD Associated body ZCMD21L08U78 ZCMD41L1 ZCMD81L5 ZCMD61M12 ZCMD21M12 ZCMD21M12 ZCMD21M12 ZCMD21L1 ZCMD2012 ZCMD21L5 ZCMD21L5 ZCMD21L1 ZCMD21L2 ZCMD21L1 ZCMD21L2 ZCMD21L1 ZCMD21L1 ZCMD21L2 ZCMD21L1 ZCMD21L1 ZCMD39L1 ZCMD21L2 ZCMD21L1 ZCMD39L1 ZCMD21L1 ZCMD39L2 ZCMD21L1 ZCMD39L5 ZCMD29L1 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L2 ZCMD25L1 ZCMD29L2 ZCMD29L1 ZCMD29L2 ZCMD21L0 ZCMD29L3 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L1 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L2 ZCMD37L5 Movement of operating head Type of operator End plunger spring return metal with nitrile boot) Type of approach Vertical approach, 1 direction	Range of Product	Telemecanique Limit switches XC Standard
Device short name ZCE	Series name	Standard format
Head type	•	Limit switch head
Product Compatibility XCKP XCKD XCKT XCMD Associated body ZCMD21L08U78 ZCMD41L1 ZCMD81L5 ZCMD61M12 ZCMD21M12 ZCMD21M12 ZCMD21L1 ZCMD21L1 ZCMD31L1 ZCMD29C12 ZCMD21L5 ZCMD21L5 ZCMD21L5 ZCMD21L2 ZCMD21L2 ZCMD21L2 ZCMD21C2 ZCMD21L1 ZCMD21C1 ZCMD21L1 ZCMD37L2 ZCMD21L1 ZCMD37L2 ZCMD29L5 ZCMD29L5 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L2 ZCMD61C12 ZCMD25L1 ZCMD25L1 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD25L5 ZCMD69C12 ZCMD69C12 ZCMD25L5 ZCMD69C12 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD69C12 ZCMD25L5 ZCMD25L5 ZCMD69C12 ZCMD25L5 ZCMD25L2 ZCMD37L5 Movement of operating head Type of operator End plunger spring return metal with nitrile boot)	Device short name	ZCE
Associated body ZCMD21L08U78 ZCMD41L1 ZCMD81L5 ZCMD61M12 ZCMD21M12 ZCMD21M1 ZCMD21L1 ZCMD21L1 ZCMD21L1 ZCMD21L5 ZCMD39L1 ZCMD39L1 ZCMD21L2 ZCMD31L1 ZCMD21L2 ZCMD21L1 ZCMD21L2 ZCMD21L1 ZCMD21L1 ZCMD21L1 ZCMD39L5 ZCMD39L5 ZCMD39L5 ZCMD39L5 ZCMD29L1 ZCMD29L5 ZCMD29L1 ZCMD29L5 ZCMD29L1 ZCMD29L5 ZCMD29L1 ZCMD29L2 ZCMD61C12 ZCMD61C12 ZCMD25L1 ZCMD39L2 ZCMD81L2 ZCMD41L5 ZCMD25L5 ZCMD60C12 ZCMD61C12 ZCMD61C12 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD25L5 ZCMD61C12 ZCMD25L5 ZCMD61C12 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L2 ZCMD37L5 Movement of operating head Type of operator End plunger spring return metal with nitrile boot)	Head type	M16 plunger head
ZCMD41L1 ZCMD81L5 ZCMD61M12 ZCMD21M12 ZCMD37L1 ZCMD81L1 ZCMD29C12 ZCMD21L5 ZCMD21L5 ZCMD21L2 ZCMD21L2 ZCMD21L1 ZCMD21L2 ZCMD21L1 ZCMD21L1 ZCMD3D21 ZCMD3D21 ZCMD3D2 ZCMD3D2 ZCMD3D2 ZCMD3D2 ZCMD3D2 ZCMD3D2 ZCMD29L5 ZCMD29L1 ZCMD29L1 ZCMD29L2 ZCMD29L1 ZCMD29L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD69C12 ZCMD69C12 ZCMD25L5 ZCMD25L5 ZCMD25L5 ZCMD25L2 ZCMD37L5 Movement of operating head Type of operator End plunger spring return metal with nitrile boot)		XCKD XCKT
Type of operator End plunger spring return metal with nitrile boot)	Associated body	ZCMD41L1 ZCMD81L5 ZCMD61M12 ZCMD21M12 ZCMD37L1 ZCMD81L1 ZCMD29C12 ZCMD21L5 ZCMD21L5 ZCMD21L5 ZCMD21L1 ZCMD21L1 ZCMD21L1 ZCMD21L1 ZCMD21L1 ZCMD21L1 ZCMD37L2 ZCMD39L5 ZCMD29L5 ZCMD29L1 ZCMD29L5 ZCMD29L1 ZCMD29L1 ZCMD29L2 ZCMD61C12 ZCMD25L1 ZCMD39L2 ZCMD81L2 ZCMD81L2 ZCMD81L2 ZCMD41L5 ZCMD25L5 ZCMD41L5 ZCMD25L5 ZCMD69C12 ZCMD69C12 ZCMD25L2
Type of operator End plunger spring return metal with nitrile boot)	Movement of operating	
Type of approach Vertical approach, 1 direction	Type of operator	End plunger spring return metal with nitrile boot)
	Type of approach	Vertical approach, 1 direction

Complementary

Environmental characteristic

Positive opening	vvitn	90
Environment		a troop
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	

Standard environment

Ordering and shipping details

Category	22413 - LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	Т
GTIN	3389110190939
Nbr. of units in pkg.	1
Package weight(Lbs)	1.83 oz (52 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	2.17 in (5.5 cm)
Package 1 Length	1.18 in (3 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Weight	18.38 oz (521 g)
Package 2 Height	5.51 in (14 cm)
Package 2 width	1.57 in (4 cm)
Package 2 Length	3.54 in (9 cm)
Unit Type of Package 3	S01
Number of Units in Package 3	50
Package 3 Weight	6.32 lb(US) (2.868 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	☑ Product Environmental Profile

Contractual warranty

Contractadi Harranty	
Warranty	18 months