# ZC2JY81

Limit switch lever, Limit switches XC Special, ZC2JY, spring with thermoplastic end, -40...70 °C



NЛ	2	ın
1 7 1	ч	

Range of Product	OsiSense XC
Series name	Special format
Product or Component Type	Limit switch lever
Device short name	ZC2J
Product Compatibility	XC2J
Associated head	ZC2JE02 ZC2JE05 ZC2JE06 ZC2JE03 ZC2JE04 ZC2JE07 ZC2JE01
Movement of operating head	Rotary
Type of operator	Spring rod lever spring return with thermoplastic end)
Type of approach	Lateral approach

## Complementary

Switch actuation	By any moving part
Positive opening	Without

#### **Environment**

Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment -40158 °F (-4070 °C) low temperature	
Ambient air temperature for storage	-40158 °F (-4070 °C) standard environment -40158 °F (-4070 °C) low temperature	
Environmental characteristic	Low temperature Standard environment	

### Ordering and shipping details

22449-LIMIT SWITCHES,ACCESSORIES	
Т	
3389110323665	
1	
1.45 oz (41.0 g)	
No	
FR	
	T 3389110323665 1 1.45 oz (41.0 g) No

## **Packing Units**

•	
Unit Type of Package 1	PCE
Package 1 Height	0.59 in (1.5 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	5.51 in (14 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	65
Package 2 Weight	6.17 lb(US) (2.798 kg)

Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

<u></u>	
Warranty	18 months