Product data sheet Characteristics

ZCKS1H29

Limit switch body, Limit switches XC Standard, ZCKS, 1NC+1 NO, snap action, M20



Main Range of Product Telemecanique Limit switches XC Standard Standard format Series name Product or Component Limit switch body Type Device short name **ZCKS** Body type Fixed Product Compatibility XCKS ZCKD06 Associated head ZCKD91 ZCKD81 ZCKD029 ZCKD39 ZCKD31 ZCKD41 ZCKD49 ZCKD33 ZCKD54 ZCKD01 ZCKD08 ZCKD34 ZCKD02 ZCKD59 ZCKD55 ZCKD05 ZCKD019 **Body Material** Cable entry 1 entry tapped for M20 x 1.5 cable gland Number of poles

1 NC + 1 NO

Snap action

1 1 position

Silver plated contacts

Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.342 x 1.5 mm ²
Positive opening	With
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.57 in (40 mm)
Height	2.87 in (73 mm)

Contacts type and

Number of steps

Contacts material

composition

Contact operation

Depth	1.42 in (36 mm)	
Net Weight	0.18 lb(US) (0.08 kg)	
Terminals description ISO n°1	(11-12)NC (21-22)NC	

Environment

IP Degree of Protection	IP65
IK Degree of Protection	IK03
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	3389110973105
Nbr. of units in pkg.	1
Package weight(Lbs)	2.47 oz (70.0 g)
Returnability	No
Country of origin	FR

Packing Units

i doking office	
Unit Type of Package 1	PCE
Package 1 Height	1.46 in (3.7 cm)
Package 1 width	1.77 in (4.5 cm)
Package 1 Length	3.07 in (7.8 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	72
Package 2 Weight	11.88 lb(US) (5.387 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

	·
147	40
vvarrantv	18 months
	To monate