# Product data sheet Characteristics

# ZCKY91TK

Limit switch lever, Limit switches XC Standard, ZCKY, spring rod with metal end, corrosive

	- 1
	- 1
	- 1
	- 11
	- 18
	- 1
	- 11
	- 1
	- 10
	- 1
	- 1
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 11
	- 44
	- 11
	- 65
	- 25
1	255
3	- 11
3	22
8	22
1	2.0
8	£1
8	- 50
а.	- 45
7	100
	1
-	
5	
~	
	CH 14,
	CH IN

# Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch lever
Device short name	ZCKY
Product Compatibility	XCKM XCKJ XCKL XCKS
Associated head	ZCKE05 ZCKD05
Movement of operating head	Rotary
Type of operator	Spring rod lever spring return with metal rod)
Type of approach	Lateral approach

## Complementary

Switch actuation	By any moving part
Positive opening	Without

#### Environment

Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment -40158 °F (-4070 °C) low temperature
Ambient air temperature for storage	-40158 °F (-4070 °C) standard environment -40158 °F (-4070 °C) low temperature
Environmental characteristic	Low temperature Corrosive

# Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ	
Discount Schedule	Т	
GTIN	3389110916409	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.74 oz (21.0 g)	
Returnability	No	
Country of origin	FR	

## **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	0.59 in (1.5 cm)	
Package 1 width	0.59 in (1.5 cm)	
Package 1 Length	6.50 in (16.5 cm)	

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Contractual warranty	

Warranty	18 months