# Product data sheet Characteristics

# **ZCKE65TK**

Limit switch head, Limit switches XC Standard, ZCKE, side steel roller plunger vertical





#### Mair

Main	
Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product Compatibility	XCKJ
Associated body	ZCKJ11H7 ZCKJ7 ZCKJ7H7 ZCKJ8 ZCKJ9H7 ZCKJD31H29 ZCKJD35 ZCKJD35 ZCKJ5 ZCKJD37 ZCKJ2H29 ZCKJ9H29 ZCKJ9H29 ZCKJ11 ZCKJD39H29 ZCKJ21 ZCKJ2H7 ZCKJ1H7 ZCKJD39 ZCKJ2H7 ZCKJBH7 ZCKJ1H29 ZCKJ5H29 ZCKJ5H29 ZCKJ5H29 ZCKJ5H29 ZCKJ5H29 ZCKJ5H29 ZCKJB39H7 ZCKJB35H7 ZCKJB35H7 ZCKJB35H7 ZCKJB35H7 ZCKJB35H7 ZCKJB35H7 ZCKJD35H7 ZCKJB37H7 ZCKJB31 ZCKJCKJCKJB31 ZCKJCKJCKJCKJCKJCKJCKJCCKJCCKJCCKJCCKJCC
Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal with vertical roller)
Type of approach	Vertical approach, 2 directions

#### Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

#### Environment

Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Corrosive

# Ordering and shipping details

10914665
10014665
10314000
oz (183.0 g)

### Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.57 in (4 cm)	
Package 1 width	1.77 in (4.5 cm)	
Package 1 Length	3.35 in (8.5 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	

# Contractual warranty

Warranty	18 months
----------	-----------