

TACT
SWITCHESNAVIGATION
SWITCHESPUSHBUTTON
SWITCHESTOGGLE
SWITCHESROCKER
SWITCHESSLIDE
SWITCHESSNAP-ACTION
SWITCHESDIP
SWITCHESKEYLOCK
SWITCHESROTARY
SWITCHESDETECTOR
SWITCHESCAP
OPTIONS

SERIES RP 3502 SWITCHES

PUSHBUTTON SWITCHES - PANEL MOUNT



FEATURES & BENEFITS

- ▶ Single Pole, Single throw with momentary function
- ▶ Rugged, Panel mount design
- ▶ Available in Nylon or metal frame body

APPLICATIONS/MARKETS

- ▶ Test & Instrumentation
- ▶ Industrial controls
- ▶ Telecommunications
- ▶ Networking

SPECIFICATIONS

Contact Rating:	3A @ 120 VAC
	1.5A @ 250 VAC
Life Expectancy (Mechanical):	6,000 cycles
Life Expectancy (Electrical):	6,000 cycles
Contact Resistance:	50mΩ (initial max.)
Insulation Resistance:	500MΩ min.
Dielectric Strength:	1,000 VAC 1 minute
Operating Temperature:	-20°C to +65°C

MATERIALS

Plastic:	Nylon (UL flame: 94V-2)
Metal:	Nickel plated brass

▶ ▶ ▶ HOW TO ORDER

SERIES	MODEL NO.	BODY STYLE	FUNCTION	BUTTON COLOR
RP	3502	None = Plastic M = Metal	A = OFF-(ON) B = ON-(OFF)	BLK = Red RED = Red GRN = Green YEL = Yellow

▶ ▶ ▶ Example Ordering Number
RP-3502-M-A-BLK

Specifications subject to change without notice.

RP 3502

