ZBZG156

Harmony XB4, Single block for test "light function", 12 and 24 V AC/DC, 24...120 V AC/ DC





Main

Main	
Range of Product	Harmony XB4 Harmony XB5
Product or Component Type	Block for test light
Product Compatibility	Integral LED BA 9s
Light block type	Single block for test light function
[Us] rated supply voltage	12 V AC/DC 24 V AC/DC 24120 V AC/DC
Electrical Connection	1 wire

Complementary

Material	Plastic
Electrical shock protection class	Class I Harmony XB4 IEC 60536 Class II Harmony XB5 IEC 60536
Net Weight	0.02 lb(US) (0.01 kg)

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Standards	UL 508	
	EN 60947-5-5	
	EN 60947-1	
	EN 60947-5-4	
	IEC 60947-5-1	
	IEC 60947-5-5	
	IEC 60947-5-4	
	CSA C22.2 No 14	
	IEC 60947-1	
	EN 60947-5-1	
	JIS C 4520	
Product Certifications	LROS (Lloyds register of shipping)	
	UL Listed	
	DNV	
	BV	
	CSA	
	GL	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms IEC 60068-2-27	
	50 gn 11 ms IEC 60068-2-27	

Ordering and shipping details

Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW	
Discount Schedule	CS2	
GTIN	3389118030107	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.63 oz (18 g)	
Returnability	No	
Country of origin	FR	

Packing Units

3	
Unit Type of Package 1	PCE
Package 1 Height	1.34 in (3.4 cm)
Package 1 width	3.46 in (8.8 cm)
Package 1 Length	2.05 in (5.2 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	165
Package 2 Weight	8.05 lb(US) (3.65 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	[™] End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months

Product data sheet Connections and Schema

ZBZG156

Wiring Diagram

