XE2NP3161

Limit switch contact block, Limit switches XC Standard, 1NC+1 NO, slow break, make before break



Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch contact block
Device short name	XE2N
Associated body	ZCT26
Number of poles	2
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break, make before break

Complementary

Product Compatibility	XCKT	
Electrical connection	Screw-clamp terminals 1 x 0.52 x 2.5 mm ²	
Contacts insulation form	Zb	
Contacts material	Silver plated contacts	
Positive opening	With	
Minimum actuation speed	6 m/min	
Contact code designation	A300, AC-15 (Ue = 240 V), le = 3 A 10 A EN/IEC 60947-5-1 appendix A Q300, DC-13 (Ue = 250 V), le = 0.27 A EN/IEC 60947-5-1 appendix A	
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3	
[Ui] rated insulation voltage	300 VUL 508 500 V 3)IEC 60947-1 300 VCSA C22.2 No 14	
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse gG	
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	

Ordering and shipping details

Ordering and shipping details	
Category	22449-LIMIT SWITCHES,ACCESSORIES
Discount Schedule	Т
GTIN	3389110196726
Nbr. of units in pkg.	1
Package weight(Lbs)	0.74 oz (21.0 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	4.33 in (11 cm)	
Package 1 width	0.98 in (2.5 cm)	
Package 1 Length	2.95 in (7.5 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope	
Environmental Disclosure	Product Environmental Profile	
Contractual warranty		

Warranty	18 months