SIEMENS

Data sheet

3SB2455-1J



Contact block and lampholder 1 NO, 1 NC, Wedge base W2 x 4.6 d, soldering pin connection

Figure similar	
product brand name	SIRIUS
product designation	contact block and lampholder
product type designation	3SB2
Contact block/ lampholder	
socket design	W2 x 4.6d
number of lampholders	1
General technical data	
product function positive opening	Yes
product component	
light source	No
suitability for integration	pushbutton / selector button
type of voltage	
 of the operating voltage 	AC/DC
protection class IP	
of the enclosure	IP40
of the terminal	IP00
vibration resistance according to IEC 60068-2-6	20 200 Hz: 5g
reference code according to IEC 81346-2	S
Substance Prohibitance (Date)	07/01/2006
operating voltage	
• at AC	
— at 50 Hz rated value	5 60 V
— at 60 Hz rated value	5 60 V
at DC rated value	5 60 V
Auxiliary circuit	
number of NC contacts for auxiliary contacts	1
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
operational current at AC-12	
 at 24 V rated value 	10 A
• at 60 V rated value	10 A
 at 110 V rated value 	10 A
 at 230 V rated value 	10 A
operational current at AC-15	
 at 24 V rated value 	4 A
• at 110 V rated value	4 A
• at 230 V rated value	4 A
operational current at DC-12	
 at 24 V rated value 	6 A

• at 60 V rated value	5 A
• at 110 V rated value	2.5 A
• at 230 V rated value	1 A
operational current at DC-13	
at 24 V rated value	3 A
 at 60 V rated value 	1.2 A
 at 110 V rated value 	0.7 A
 at 230 V rated value 	0.3 A
Connections/ Terminals	
type of electrical connection	solder pin connectors
Ambient conditions	
ambient temperature	
 during operation 	-25 +60 °C
 during storage 	-40 +80 °C
nstallation/ mounting/ dimensions	
fastening method	clip-on
height	19 mm
width	18 mm
depth	29 mm
Certificates/ approvals	











CE EG-Konf.

other

Confirmation

	acided to exit the Russian market (see here). nens.com/global/en/pressrelease/siemens-wind-down-russian-business
Please contact y	king on the renewal of the current EAC certificates. Your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to ar arket (other than the sanctioned EAEU member states Russia or Belarus).
Information on	
	dustry.siemens.com/cs/ww/en/view/109813875
https://www.siem	d Downloadcenter (Catalogs, Brochures,)
	Online ordering system) stry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2455-1J
Cax online gene	
-	tomation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2455-1J
Service&Suppo	rt (Manuals, Certificates, Characteristics, FAQs,) idustry.siemens.com/cs/ww/en/ps/3SB2455-1J
	e (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) nation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2455-1J⟨=en

last modified:

1/18/2021 🖸