Product data sheet Characteristics

ZBZM156

Main

Harmony XB4, Block for test "light function" with integral LED, double, 48...230 V AC





| Range of Product | Harmony XB5 Harmony XB4 |
|------------------------------|--------------------------------------|
| Product or Component Type | Block for test light |
| Product Compatibility | Integral LED |
| Light block type | Double block for test light function |
| [Us] rated supply voltage | 48230 V AC |
| Electrical Connection | Wires |

Complementary

| Complementary | | |
|---------------------------------------|---|--|
| Material | Plastic | |
| Electrical shock protection class | Class I Harmony XB4 IEC 60536 Class II Harmony XB5 IEC 60536 | |
| Net Weight | 0.02 lb(US) (0.01 kg) | |
| Environment | | |
| Ambient Air Temperature for Storage | -40158 °F (-4070 °C) | |
| Ambient air temperature for operation | -13158 °F (-2570 °C) | |
| Standards | EN 60947-1 EN 60947-5-4 IEC 60947-5-4 IEC 60947-5-1 CSA C22.2 No 14 UL 508 EN 60947-5-5 IEC 60947-5-5 EN 60947-5-1 JIS C 4520 IEC 60947-1 | |
| Product Certifications | DNV GL LROS (Lloyds register of shipping) UL Listed BV CSA | |
| Vibration resistance | 5 gn 2500 Hz)IEC 60068-2-6 | |
| Shock resistance | 30 gn 18 ms IEC 60068-2-27 50 gn 11 ms IEC 60068-2-27 | |

Ordering and shipping details

| Category | 22469 - PUSHBUTTON,22MM ACCESSORIES-NEW |
|-----------------------|---|
| Discount Schedule | CS2 |
| GTIN | 3389118030114 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.02 oz (29 g) |
| Returnability | No |
| Country of origin | FR |
| | |



Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------------------|
| Package 1 Height | 2.09 in (5.3 cm) |
| Package 1 width | 1.34 in (3.4 cm) |
| Package 1 Length | 3.46 in (8.8 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Weight | 3.93 lb(US) (1.784 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | ₽ Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | Provide the Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

Warranty

18 months

Wiring Diagram

