# 9001KYG1

30mm push button, Type K, guarded enclosure, one opening, integral guard, gray, NEMA 1, 3, 4, 13





Main	
Range of Product	Harmony 9001K Harmony 9001SK
Product or Component Type	Empty enclosure
Device short name	9001K
Number of cut-out	1 cut-out
Cable entry	1 entry tapped for 3/4" cable gland

Complementary

Product destination	For Ø 30 mm control and signalling units
Material	Aluminium
Colour of cover	Grey
Net Weight	2.65 lb(US) (1.2 kg)

#### **Environment**

Protective treatment	TH
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Overvoltage category	II IEC 61140
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 3 NEMA 4 NEMA 6

## Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	785901589099
Nbr. of units in pkg.	1
Package weight(Lbs)	2.99 lb(US) (1.356 kg)
Returnability	No
Country of origin	MX

#### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	4.20 in (10.668 cm)	
Package 1 width	4.90 in (12.446 cm)	
Package 1 Length	6.10 in (15.494 cm)	

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months
----------	-----------

# Product data sheet Dimensions Drawings

# 9001KYG1

#### **Dimensions**



