XKMA991

contact block - standard contact blow-out - compatible with XKM



Main	
Product or Component Type	Controllers separate parts
Accessory / separate part category	Control accessory
Product Specific Application	Heavy hoisting applications
Product Compatibility	XKM
Accessory / Separate Part Type	Contact block
Number of contacts	4
Contact blow-out type	Standard

Complementary

lectrical connection Screw clamp terminal 1 x 1.52 x 2.5 mm ²		
Contact operation	Slow-break Double-break	
[Ith] conventional free air thermal current	20 A IEC 337-1 20 A NF C 63-140 20 A VDE 0660	
[Ui] rated insulation voltage	500 V AC/DC IEC 158-1 500 V AC/DC NF C 20-040 500 V AC/DC VDE 0110 600 V CSA C22.2 No 14	
Positive opening	With	
Maximum resistance across terminals	25 MOhm 1 A NF C 93-050	
Short-circuit protection	20 A cartridge fuse gG IEC 337-1B 20 A cartridge fuse gG VDE 0660 part 2	
Electrical durability	3000000 Cycles DC inductive 120 V 75 IEC 337-1 DC-11 60 cyc/mn 0.5 3000000 Cycles DC inductive 24 V 70 IEC 337-1 DC-11 60 cyc/mn 0.5 3000000 cycles DC inductive 48 V 75 IEC 337-1 DC-11 60 cyc/mn 0.5	
Net Weight	0.68 lb(US) (0.31 kg)	

Environment

Standards CLINELEC LIN 300 13	Standards	CENELEC EN 50013
-------------------------------	-----------	------------------

Ordering and shipping details

Category	22474 - PUSHBUTTON,CRANE JOYSTICKS	
Discount Schedule	I	
GTIN	3389110661309	
Nbr. of units in pkg.	1	
Package weight(Lbs)	11.32 oz (321 g)	
Returnability	No	
Country of origin	FR	

Packing Units

•		
Unit Type of Package 1	PCE	
Package 1 Height	2.17 in (5.5 cm)	
Package 1 width	3.54 in (9 cm)	
Package 1 Length	6.10 in (15.5 cm)	
Unit Type of Package 2	S03	
Number of Units in Package 2	26	
Package 2 Weight	19.32 lb(US) (8.762 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☐ China RoHS Declaration	

Contractual warranty

Warranty	18 montl	