SIEMENS

Data sheet

3SE5000-0AE05



Actuator head for position switch 3SE51/52 EN 50041, Roller lever Metal lever and Plastic roller 22 mm

product brand name	SIRIUS		
product designation	actuator head for position swite	ch	
product type designation	3SE5		
manufacturer's article number			
 of the supplied actuator head for position switches 	<u>3SE5000-0AE05</u>		
General technical data			
product function positive opening	Yes		
shock resistance			
 according to IEC 60068-2-27 	30g / 11 ms		
vibration resistance			
 according to IEC 60068-2-6 	0.35 mm/5g		
mechanical service life (operating cycles) typical	15 000 000		
material of the enclosure of the switch head	plastic		
reference code according to IEC 81346-2	Т		
active principle	mechanical		
Substance Prohibitance (Date)	07/01/2006		
minimum actuating force in directions of actuation	10 N		
Ambient conditions			
ambient temperature			
 during operation 	-25 +85 °C		
during storage	-40 +90 °C		
explosion protection category for dust	none		
Enclosure			
coating of the enclosure	Other types		
Drive Head			
design of the actuating element	Roller lever, plastic roller		
standard-compliant actuator head	EN 50041		
shape of the switch head	roller		
outer diameter of the switch head	22 mm		
Installation/ mounting/ dimensions			
mounting position	any		
fastening method	lockable plug-in fixing		
design of the interface for safety-related communication	without		
Communication/ Protocol			
design of the interface	without		
Certificates/ approvals			
General Product Approval		Functional Safety/Safety of Ma- chinery	Declaration of Con- formity

(SP)	<u>Confirmation</u>	SAN UR	EAC	<u>Type Examination Cer-</u> <u>tificate</u>	UK CA
Declaration of Con- formity	Test Certificates	other			
CE EG-Konf.	<u>Type Test Certific-</u> ates/Test Report	<u>Confirmation</u>			
rther information					
formation- and Dow ttps://www.siemens.cc dustry Mall (Online ttps://mall.industry.sie ax online generator ttp://support.automatic ervice&Support (Mal	siemens.com/cs/ww/en/v mloadcenter (Catalogs, om/ic10 ordering system) mens.com/mall/en/en/Cat	Brochures,) talog/product?mlfb=3SE5(Korder/default.aspx?lang= racteristics, FAQs,)		<u>=05</u>	
mage database (prod	luct images, 2D dimensi	ion drawings, 3D models de.aspx?mlfb=3SE5000-0	s, device circuit diagra AE05⟨=en	ams, EPLAN macros,)	
		19.8			
	_			9	-
4					

12/21/2020 🖸