





APPROVED: _____

DATE: _____ TITLE: _____



Rev	AWO #	Description	Date	Appr
-		RELEASED	10/26/20	
A		UPDATE SPEC.	8/31/21	WX/RC



SOLID COLOR WITH
WHITE MARKINGS
(See Chart)



CIRCUIT DIAGRAM
(SPDT) ON-OFF-ON



SW-R2-2E-F-XX-8

	Body Color
BLANK	Standard Black
W	White

	Actuator Markings
6	

SPECIFICATIONS:

Body: Nylon 66, Color Black, Rated UL 94V-0

Terminal: Brass, Silver plated

Button: Nylon 66, Solid color, White color markings. (See Chart)

Electrical:

The rated load: 250V AC, 6A

125V AC, 10A

Contact resistance: 50 mohms max

Insulation resistance: 100 Mohms min

Dielectric withstanding voltage: 1500 VAC/5S min

Mechanical:

Electrical life: 10000 Cycles min

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant



Replace "x" in P/N with the corresponding switch color and marking

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES
.X ± .10 Ø.X ± .10
.XX ± .020 Ø.XX ± .015
.XXX ± .015 Ø.XXX ± .010

APPROVALS		DATE
DRAWN	OW	10/26/20
CHECKED	AC	10/26/20
APPROVED		

ADAM
TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE
SWITCH, MINIATURE ROCKER, SPDT,
ON-OFF-ON, QC .187 [4.75MM]

SIZE	PART NO.	REV.
X	SW-R2-2E-F-XX-8	A
REF:	S00206C	SCALE: NTS
SHEET 1 OF 1		