

AC AXIAL FAN 120x120x38mm



Housing: Die-Cast Aluminum, Painted Black
Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 1500VAC for one minute
Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~85°C(Humidity 35%-85%RH)
Motor Protection: Impedance Protected
Weight: 520 g **Packing:** 40PCS/CTN

Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1238B11T5-96	115	50/60	75.1/75.1	3.9/3.9	29.6/34.5	2,300/2,300	150/130	12/10	B,S	①/②
FA1238B11T7-96	115	50/60	80.2/95.4	6.7/8.0	39.4/44.3	2,600/2,900	260/220	19/16	B,S	③/④
FA1238B22T5-96	230	50/60	75.1/63.9	3.9/3.4	33.5/29.6	2,300/2,100	60/50	10/9	B,S	①/②
FA1238B22T7-96	230	50/60	80.2/91.4	6.7/7.5	39.4/46.3	2,600/2,800	100/90	15/13	B,S	③/④

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

