

Standards and Specifications
of
Model: FBD1232B48W5-81-2R
(Auto Restart Protection)

A. General Specification

Item	Specification / Standard / Condition	
Outline Dimension	120 mm x 120 mm x 32 mm	
Bearing	Dual Ball Bearing	
Rated Voltage	DC 48 V	
Operating Voltage	DC 24.00 V ~ DC 52.80 V	
Starting Voltage	DC 24.00 V	1. Rated Voltage 2. 25°C, 65% RH
Actual Current	0.24 A	
Rated Current	0.20 A	
Power Consumption	11.52 W	
Speed	2,500 R.P.M.	1. Free Air 2. Rated Voltage 3. 25°C, 65% RH 4. Tolerance: ± 10%
Maximum Airflow	34.30 CFM	1. Rated Voltage 2. AMCA Standard 3. Rated Current
Maximum Static Pressure	16.60 mm-H ₂ O	
Noise Level	50.70 dB (A)	1. Rated Voltage 2. Measured in a Non-Echo Chamber 3. CNS 8753 Standard 4. ISO 3744 Test Condition
Life	80,000 hrs	40°C, L10 at Conf. Level 90%, Rated Voltage
Net Weight	315 g	
Number of Pole	4 Poles	
Rotating Direction	Counter-Clockwise	
Plastic Material: Blade, Housing, Bobbin	1. UL 94V-0 2. P.B.T. + 30% GF Black	
Lead Wire	UL 1007, 26 AWG	Red: (+) Black: (-)
Connector		

B. Electrical Specification

Item	Specification / Condition
Locked Rotor Protection	a. Auto power off after locked at rated voltage for 1 sec. b. After auto power off, circuit attempt to restart in 2-6 sec.
Polarity Protection	Circuit is protected when V _{CC} & GND are exchanged.
Insulation Resistance	10 m.Ω / between unshielded wire and frame at 500 VDC/min.
Dielectric Strength	5 mA Maximum. / Measured between lead wire + and frame at 500 VAC/min.

C. Environmental Specification


Item	Specification / Condition
Operating Condition	Temperature: -20°C ~ + 70°C Humidity: 15% ~ 90% RH
Storage Temperature	Temperature: -40°C ~ + 85°C Humidity: 15% ~ 90% RH
Humidity	Per MIL-STD-202F Method 103B Life: 96 hours Temperature: +40 ± 2°C
Thermal Shock	Per MIL-STD-202F Method 107D, Condition D
Packing Vibration Test	Packing condition: X, Y, Z 3 directions, 1.1G load vibration test for 30 min.
Packing Shock Proof Test	1 corner, 3 edges, 6 faces natural drop from 60cm high, packed

D. Safety Approvals





Safety Approval	File No.
UL	E194726
CUL	E194726
TUV	R50048194

E. Label Marking



(1)	Model Number
(2)	Rated Voltage
(3)	Power Consumption
(4)	Bearing Type
(5)	Location

F. Air Flow Performance Curve**G. Model Drawing**

H. Fan Photos



FBD1232-81