

1		2		3		4		5		6		7																																																																																																					
A	<table><thead><tr><th colspan="2">Properties</th><th>Value</th><th>Unit</th><th>Tolerance</th><th>Test Method</th></tr></thead><tbody><tr><td colspan="2">Thermal Conductivity</td><td>6</td><td>W/m·K</td><td>± 0.3</td><td>ASTM D5470</td></tr><tr><td colspan="2">Reinforcement Carrier optional</td><td>Fiberglass mesh</td><td>/</td><td>/</td><td>/</td></tr><tr><td colspan="2">Color*</td><td>Gray white</td><td>/</td><td>/</td><td>Visual</td></tr><tr><td colspan="2">Density</td><td>3.1</td><td>g/cm³</td><td>/</td><td>ASTM D792</td></tr><tr><td colspan="2">Hardness*</td><td>50</td><td>Shore00</td><td>± 5</td><td>ASTM D2240</td></tr><tr><td colspan="2">Tensile strength</td><td>20</td><td>psi</td><td>/</td><td>ASTM D412</td></tr><tr><td colspan="2">Flame Rating</td><td>94V-0</td><td>/</td><td>/</td><td>Equivalent UL</td></tr><tr><td colspan="2">Volume Resistance</td><td>1.25 x 10¹³</td><td>Ω·cm</td><td>/</td><td>ASTM D257</td></tr><tr><td colspan="2">Breakdown Voltage</td><td>≥ 5</td><td>KV/mm</td><td>/</td><td>ASTM D149</td></tr></tbody></table>												Properties		Value	Unit	Tolerance	Test Method	Thermal Conductivity		6	W/m·K	± 0.3	ASTM D5470	Reinforcement Carrier optional		Fiberglass mesh	/	/	/	Color*		Gray white	/	/	Visual	Density		3.1	g/cm³	/	ASTM D792	Hardness*		50	Shore00	± 5	ASTM D2240	Tensile strength		20	psi	/	ASTM D412	Flame Rating		94V-0	/	/	Equivalent UL	Volume Resistance		1.25 x 10 ¹³	Ω·cm	/	ASTM D257	Breakdown Voltage		≥ 5	KV/mm	/	ASTM D149	Notes: 1. Adhesivity 1.1. Natural tacky 2. Features 2.1. Good thermal conductivity, low thermal resistance 2.2. Good thermal stability 2.3. Good resilience; high reliability for long-term use 2.4. Good insulating material 3. Application options 3.1. Communication equipment, Network terminals, Storage devices, Consumer electronics, power supply devices, security equipment	A																																							
	Properties		Value	Unit	Tolerance	Test Method																																																																																																											
	Thermal Conductivity		6	W/m·K	± 0.3	ASTM D5470																																																																																																											
	Reinforcement Carrier optional		Fiberglass mesh	/	/	/																																																																																																											
	Color*		Gray white	/	/	Visual																																																																																																											
	Density		3.1	g/cm³	/	ASTM D792																																																																																																											
	Hardness*		50	Shore00	± 5	ASTM D2240																																																																																																											
	Tensile strength		20	psi	/	ASTM D412																																																																																																											
	Flame Rating		94V-0	/	/	Equivalent UL																																																																																																											
	Volume Resistance		1.25 x 10 ¹³	Ω·cm	/	ASTM D257																																																																																																											
Breakdown Voltage		≥ 5	KV/mm	/	ASTM D149																																																																																																												
B	<table><tbody><tr><td rowspan="2">Storage conditions</td><td>Temperature (T)</td><td>15 < T < 30</td><td>°C</td><td>/</td><td>/</td></tr><tr><td>Relative humidity (Rh)</td><td>< 70</td><td>%</td><td>/</td><td>/</td></tr><tr><td colspan="2">Shelf life</td><td>12</td><td>months</td><td>/</td><td>/</td></tr></tbody></table>												Storage conditions	Temperature (T)	15 < T < 30	°C	/	/	Relative humidity (Rh)	< 70	%	/	/	Shelf life		12	months	/	/	B																																																																																			
	Storage conditions	Temperature (T)	15 < T < 30	°C	/	/																																																																																																											
		Relative humidity (Rh)	< 70	%	/	/																																																																																																											
	Shelf life		12	months	/	/																																																																																																											
	C	Additional adhesive surface or reinforcement can influence the thermal conductivity. Modification of color or hardness can influence the thermal conductivity. A suitability check is recommended. * other on request												C																																																																																																			
		D	x y z <table><thead><tr><th>Properties</th><th>Min (mm)</th><th>Max (mm)</th></tr></thead><tbody><tr><td>Length (x)</td><td>5.0</td><td>400.0</td></tr><tr><td>Width (y)</td><td>5.0</td><td>350.0</td></tr><tr><td>Thickness (z)</td><td>0.5</td><td>10.0</td></tr></tbody></table> ① Special or other dimensions / sizes on request.												Properties	Min (mm)	Max (mm)	Length (x)	5.0	400.0	Width (y)	5.0	350.0	Thickness (z)	0.5	10.0	D																																																																																						
			Properties	Min (mm)	Max (mm)																																																																																																												
			Length (x)	5.0	400.0																																																																																																												
			Width (y)	5.0	350.0																																																																																																												
			Thickness (z)	0.5	10.0																																																																																																												
E			Order code: VFSFAx-xxxxyyzzz-xy ① Length (x): 005: 5mm (min) 400: 400mm (max) Width (y): 005: 5mm (min) 350: 350mm (max) Thickness (z): 005: 0.5mm (min) 100: 10.0mm (max) 0: Width y.0mm 5: Width y.5mm 0: Length x.0mm 5: Length x.5mm												E																																																																																																		
			F	N: Not reinforced / not adhesive / natrual tack O: Not reinforced / one side adhesive P: Not reinforced / two sides adhesive R: Reinforced / not adhesive / natrual tack S: Reinforced / one side adhesive T: Reinforced / two sides adhesive												F																																																																																																	
				G	<table><thead><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th></th><th>Date</th><th>Name</th><th>Description:</th></tr></thead><tbody><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>08.08.2022</td><td>Segal</td><td>Thermal foil, containing silicone, Gray white</td></tr><tr><td>0~30</td><td>±0.3</td><td></td><td></td><td></td><td></td><td></td><td>Approved</td><td>08.05.2024</td><td>Segal</td><td>ASSMANN WSW-No.</td></tr><tr><td>31~50</td><td>±0.5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>VFSFAx-xxxxyyzzz-xy</td></tr><tr><td>51~400</td><td>±2.0</td><td>②</td><td>Add the standard P/N in page 2 to 4</td><td>08.05.2024</td><td>Segal</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>①</td><td>Update</td><td>03.11.2022</td><td>Larsen</td><td rowspan="3">ASSMANN WSW components A company of BCS</td><td colspan="2">Drawing-No.</td><td rowspan="3">ASS 4997 HS</td><td rowspan="3">rev02</td></tr><tr><td>0~1</td><td>±0.1</td><td></td><td></td><td></td><td></td><td colspan="2"></td></tr><tr><td>1~10</td><td>±10%</td><td>③</td><td>Drawn</td><td>08.08.2022</td><td>Segal</td><td colspan="2"></td></tr><tr><td>T</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="2">Customer-No.</td><td colspan="3">SHEET 1 / 4</td></tr></tbody></table>												Scale	Free						Date	Name	Description:		TOLERANCE							Drawn	08.08.2022	Segal	Thermal foil, containing silicone, Gray white	0~30	±0.3						Approved	08.05.2024	Segal	ASSMANN WSW-No.	31~50	±0.5									VFSFAx-xxxxyyzzz-xy	51~400	±2.0	②	Add the standard P/N in page 2 to 4	08.05.2024	Segal						DIM	TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS	Drawing-No.		ASS 4997 HS	rev02	0~1	±0.1							1~10	±10%	③	Drawn	08.08.2022	Segal			T	TOL	Id.	Modification	Date	Name	Customer-No.		SHEET 1 / 4			G			
					Scale	Free						Date	Name				Description:																																																																																																
	TOLERANCE									Drawn	08.08.2022	Segal	Thermal foil, containing silicone, Gray white																																																																																																				
	0~30	±0.3								Approved	08.05.2024	Segal	ASSMANN WSW-No.																																																																																																				
	31~50	±0.5											VFSFAx-xxxxyyzzz-xy																																																																																																				
	51~400	±2.0			②	Add the standard P/N in page 2 to 4	08.05.2024	Segal																																																																																																									
	DIM	TOL			①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS	Drawing-No.		ASS 4997 HS	rev02																																																																																																				
	0~1	±0.1																																																																																																															
1~10	±10%	③			Drawn	08.08.2022	Segal																																																																																																										
T	TOL	Id.	Modification		Date	Name	Customer-No.		SHEET 1 / 4																																																																																																								
H	RoHS compliant Unit:mm												H																																																																																																				
	<table><thead><tr><th>1</th><th>2</th><th>3</th><th>4</th><th>5</th><th>6</th><th>7</th></tr></thead></table>													1	2	3	4	5	6	7																																																																																													
	1	2	3	4	5	6	7																																																																																																										

	1	2	3	4	5	6	7																																																																																																																														
A	Standard articles <table><tr><td>②</td><td>Article number</td><td>Length [mm]</td><td>Width [mm]</td><td>Thickness [mm]</td></tr><tr><td></td><td>VFSFAN-015015005-00</td><td>15</td><td>15</td><td>0.5</td></tr><tr><td></td><td>VFSFAN-015015010-00</td><td>15</td><td>15</td><td>1.0</td></tr><tr><td></td><td>VFSFAN-015015015-00</td><td>15</td><td>15</td><td>1.5</td></tr><tr><td></td><td>VFSFAN-015015020-00</td><td>15</td><td>15</td><td>2.0</td></tr><tr><td></td><td>VFSFAN-015015030-00</td><td>15</td><td>15</td><td>3.0</td></tr><tr><td></td><td>VFSFAN-015015040-00</td><td>15</td><td>15</td><td>4.0</td></tr><tr><td></td><td>VFSFAN-030030005-00</td><td>30</td><td>30</td><td>0.5</td></tr><tr><td></td><td>VFSFAN-030030010-00</td><td>30</td><td>30</td><td>1.0</td></tr><tr><td></td><td>VFSFAN-030030015-00</td><td>30</td><td>30</td><td>1.5</td></tr><tr><td></td><td>VFSFAN-030030020-00</td><td>30</td><td>30</td><td>2.0</td></tr><tr><td></td><td>VFSFAN-030030030-00</td><td>30</td><td>30</td><td>3.0</td></tr><tr><td></td><td>VFSFAN-030030040-00</td><td>30</td><td>30</td><td>4.0</td></tr><tr><td></td><td>VFSFAN-050050005-00</td><td>50</td><td>50</td><td>0.5</td></tr><tr><td></td><td>VFSFAN-050050010-00</td><td>50</td><td>50</td><td>1.0</td></tr><tr><td></td><td>VFSFAN-050050015-00</td><td>50</td><td>50</td><td>1.5</td></tr><tr><td></td><td>VFSFAN-050050020-00</td><td>50</td><td>50</td><td>2.0</td></tr><tr><td></td><td>VFSFAN-050050030-00</td><td>50</td><td>50</td><td>3.0</td></tr><tr><td></td><td>VFSFAN-050050040-00</td><td>50</td><td>50</td><td>4.0</td></tr><tr><td></td><td>VFSFAN-100100005-00</td><td>100</td><td>100</td><td>0.5</td></tr><tr><td></td><td>VFSFAN-100100010-00</td><td>100</td><td>100</td><td>1.0</td></tr><tr><td></td><td>VFSFAN-100100015-00</td><td>100</td><td>100</td><td>1.5</td></tr><tr><td></td><td>VFSFAN-100100020-00</td><td>100</td><td>100</td><td>2.0</td></tr><tr><td></td><td>VFSFAN-100100030-00</td><td>100</td><td>100</td><td>3.0</td></tr><tr><td></td><td>VFSFAN-100100040-00</td><td>100</td><td>100</td><td>4.0</td></tr></table>							②	Article number	Length [mm]	Width [mm]	Thickness [mm]		VFSFAN-015015005-00	15	15	0.5		VFSFAN-015015010-00	15	15	1.0		VFSFAN-015015015-00	15	15	1.5		VFSFAN-015015020-00	15	15	2.0		VFSFAN-015015030-00	15	15	3.0		VFSFAN-015015040-00	15	15	4.0		VFSFAN-030030005-00	30	30	0.5		VFSFAN-030030010-00	30	30	1.0		VFSFAN-030030015-00	30	30	1.5		VFSFAN-030030020-00	30	30	2.0		VFSFAN-030030030-00	30	30	3.0		VFSFAN-030030040-00	30	30	4.0		VFSFAN-050050005-00	50	50	0.5		VFSFAN-050050010-00	50	50	1.0		VFSFAN-050050015-00	50	50	1.5		VFSFAN-050050020-00	50	50	2.0		VFSFAN-050050030-00	50	50	3.0		VFSFAN-050050040-00	50	50	4.0		VFSFAN-100100005-00	100	100	0.5		VFSFAN-100100010-00	100	100	1.0		VFSFAN-100100015-00	100	100	1.5		VFSFAN-100100020-00	100	100	2.0		VFSFAN-100100030-00	100	100	3.0		VFSFAN-100100040-00	100	100	4.0	A
②								Article number	Length [mm]	Width [mm]	Thickness [mm]																																																																																																																										
								VFSFAN-015015005-00	15	15	0.5																																																																																																																										
								VFSFAN-015015010-00	15	15	1.0																																																																																																																										
								VFSFAN-015015015-00	15	15	1.5																																																																																																																										
								VFSFAN-015015020-00	15	15	2.0																																																																																																																										
								VFSFAN-015015030-00	15	15	3.0																																																																																																																										
								VFSFAN-015015040-00	15	15	4.0																																																																																																																										
								VFSFAN-030030005-00	30	30	0.5																																																																																																																										
								VFSFAN-030030010-00	30	30	1.0																																																																																																																										
								VFSFAN-030030015-00	30	30	1.5																																																																																																																										
								VFSFAN-030030020-00	30	30	2.0																																																																																																																										
								VFSFAN-030030030-00	30	30	3.0																																																																																																																										
								VFSFAN-030030040-00	30	30	4.0																																																																																																																										
								VFSFAN-050050005-00	50	50	0.5																																																																																																																										
								VFSFAN-050050010-00	50	50	1.0																																																																																																																										
								VFSFAN-050050015-00	50	50	1.5																																																																																																																										
								VFSFAN-050050020-00	50	50	2.0																																																																																																																										
								VFSFAN-050050030-00	50	50	3.0																																																																																																																										
								VFSFAN-050050040-00	50	50	4.0																																																																																																																										
								VFSFAN-100100005-00	100	100	0.5																																																																																																																										
								VFSFAN-100100010-00	100	100	1.0																																																																																																																										
								VFSFAN-100100015-00	100	100	1.5																																																																																																																										
								VFSFAN-100100020-00	100	100	2.0																																																																																																																										
								VFSFAN-100100030-00	100	100	3.0																																																																																																																										
								VFSFAN-100100040-00	100	100	4.0																																																																																																																										
B															B																																																																																																																						
C															C																																																																																																																						
D								D																																																																																																																													
E								E																																																																																																																													
F								F																																																																																																																													
G	RoHS compliant Unit:mm		Scale	Free				Date	Name	Description: Thermal foil, containing silicone, Gray white	ASSMANN WSW-No. VFSFAX-xxxxyyyzzz-xy	G																																																																																																																									
TOLERANCE						Drawn	08.08.2022	Segal																																																																																																																													
0~30			±0.3				Approved	08.05.2024	Segal																																																																																																																												
31~50			±0.5																																																																																																																																		
51~400			±2.0	②	Add the standard P/N in page 2 to 4	08.05.2024	Segal																																																																																																																														
DIM			TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS		Drawing-No. ASS 4997 HS		rev02	H																																																																																																																								
0~1			±0.1																																																																																																																																		
1~10			±10%	③	Drawn	08.08.2022	Segal			Customer-No.		SHEET 2 / 4																																																																																																																									
H				T	TOL	Id.	Modification	Date	Name																																																																																																																												
	1	2	3	4	5	6	7																																																																																																																														

		1	2	3	4	5	6	7																																																																																																								
A	Standard articles	<table><tr><td>②</td><td>Article number</td><td>Length [mm]</td><td>Width [mm]</td><td>Thickness [mm]</td></tr><tr><td>VFSFAN-150150005-00</td><td>150</td><td>150</td><td>0.5</td></tr><tr><td>VFSFAN-150150010-00</td><td>150</td><td>150</td><td>1.0</td></tr><tr><td>VFSFAN-150150015-00</td><td>150</td><td>150</td><td>1.5</td></tr><tr><td>VFSFAN-150150020-00</td><td>150</td><td>150</td><td>2.0</td></tr><tr><td>VFSFAN-150150030-00</td><td>150</td><td>150</td><td>3.0</td></tr><tr><td>VFSFAN-150150040-00</td><td>150</td><td>150</td><td>4.0</td></tr><tr><td>VFSFAR-015015005-00</td><td>15</td><td>15</td><td>0.5</td></tr><tr><td>VFSFAR-015015010-00</td><td>15</td><td>15</td><td>1.0</td></tr><tr><td>VFSFAR-015015015-00</td><td>15</td><td>15</td><td>1.5</td></tr><tr><td>VFSFAR-015015020-00</td><td>15</td><td>15</td><td>2.0</td></tr><tr><td>VFSFAR-015015030-00</td><td>15</td><td>15</td><td>3.0</td></tr><tr><td>VFSFAR-015015040-00</td><td>15</td><td>15</td><td>4.0</td></tr><tr><td>VFSFAR-030030005-00</td><td>30</td><td>30</td><td>0.5</td></tr><tr><td>VFSFAR-030030010-00</td><td>30</td><td>30</td><td>1.0</td></tr><tr><td>VFSFAR-030030015-00</td><td>30</td><td>30</td><td>1.5</td></tr><tr><td>VFSFAR-030030020-00</td><td>30</td><td>30</td><td>2.0</td></tr><tr><td>VFSFAR-030030030-00</td><td>30</td><td>30</td><td>3.0</td></tr><tr><td>VFSFAR-030030040-00</td><td>30</td><td>30</td><td>4.0</td></tr><tr><td>VFSFAR-050050005-00</td><td>50</td><td>50</td><td>0.5</td></tr><tr><td>VFSFAR-050050010-00</td><td>50</td><td>50</td><td>1.0</td></tr><tr><td>VFSFAR-050050015-00</td><td>50</td><td>50</td><td>1.5</td></tr><tr><td>VFSFAR-050050020-00</td><td>50</td><td>50</td><td>2.0</td></tr><tr><td>VFSFAR-050050030-00</td><td>50</td><td>50</td><td>3.0</td></tr><tr><td>VFSFAR-050050040-00</td><td>50</td><td>50</td><td>4.0</td></tr></table>									②	Article number	Length [mm]	Width [mm]	Thickness [mm]	VFSFAN-150150005-00	150	150	0.5	VFSFAN-150150010-00	150	150	1.0	VFSFAN-150150015-00	150	150	1.5	VFSFAN-150150020-00	150	150	2.0	VFSFAN-150150030-00	150	150	3.0	VFSFAN-150150040-00	150	150	4.0	VFSFAR-015015005-00	15	15	0.5	VFSFAR-015015010-00	15	15	1.0	VFSFAR-015015015-00	15	15	1.5	VFSFAR-015015020-00	15	15	2.0	VFSFAR-015015030-00	15	15	3.0	VFSFAR-015015040-00	15	15	4.0	VFSFAR-030030005-00	30	30	0.5	VFSFAR-030030010-00	30	30	1.0	VFSFAR-030030015-00	30	30	1.5	VFSFAR-030030020-00	30	30	2.0	VFSFAR-030030030-00	30	30	3.0	VFSFAR-030030040-00	30	30	4.0	VFSFAR-050050005-00	50	50	0.5	VFSFAR-050050010-00	50	50	1.0	VFSFAR-050050015-00	50	50	1.5	VFSFAR-050050020-00	50	50	2.0	VFSFAR-050050030-00	50	50	3.0	VFSFAR-050050040-00	50	50	4.0	A
②											Article number	Length [mm]	Width [mm]	Thickness [mm]																																																																																																		
VFSFAN-150150005-00											150	150	0.5																																																																																																			
VFSFAN-150150010-00											150	150	1.0																																																																																																			
VFSFAN-150150015-00											150	150	1.5																																																																																																			
VFSFAN-150150020-00											150	150	2.0																																																																																																			
VFSFAN-150150030-00											150	150	3.0																																																																																																			
VFSFAN-150150040-00											150	150	4.0																																																																																																			
VFSFAR-015015005-00											15	15	0.5																																																																																																			
VFSFAR-015015010-00											15	15	1.0																																																																																																			
VFSFAR-015015015-00											15	15	1.5																																																																																																			
VFSFAR-015015020-00											15	15	2.0																																																																																																			
VFSFAR-015015030-00											15	15	3.0																																																																																																			
VFSFAR-015015040-00											15	15	4.0																																																																																																			
VFSFAR-030030005-00											30	30	0.5																																																																																																			
VFSFAR-030030010-00											30	30	1.0																																																																																																			
VFSFAR-030030015-00											30	30	1.5																																																																																																			
VFSFAR-030030020-00											30	30	2.0																																																																																																			
VFSFAR-030030030-00											30	30	3.0																																																																																																			
VFSFAR-030030040-00											30	30	4.0																																																																																																			
VFSFAR-050050005-00											50	50	0.5																																																																																																			
VFSFAR-050050010-00											50	50	1.0																																																																																																			
VFSFAR-050050015-00											50	50	1.5																																																																																																			
VFSFAR-050050020-00											50	50	2.0																																																																																																			
VFSFAR-050050030-00											50	50	3.0																																																																																																			
VFSFAR-050050040-00											50	50	4.0																																																																																																			
B											B																																																																																																					
C											C																																																																																																					
D	D																																																																																																															
E	E																																																																																																															
F	F																																																																																																															
G	RoHS compliant Unit:mm	Scale	Free					Date	Name	Description: Thermal foil, containing silicone, Gray white	ASSMANN WSW-No. VFSFAX-xxxxyyyzzz-xy	G																																																																																																				
		TOLERANCE					Drawn	08.08.2022	Segal																																																																																																							
		0~30	±0.3				Approved	08.05.2024	Segal																																																																																																							
		31~50	±0.5																																																																																																													
		51~400	±2.0	②	Add the standard P/N in page 2 to 4	08.05.2024	Segal																																																																																																									
		DIM	TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS		Drawing-No. ASS 4997 HS		rev02																																																																																																				
		0~1	±0.1				Segal																																																																																																									
		1~10	±10%	③	Drawn	08.08.2022																																																																																																										
		T	TOL	Id.	Modification	Date	Name	Customer-No.		SHEET 3 / 4																																																																																																						
	1	2	3	4	5	6	7																																																																																																									

	1	2	3	4	5	6	7																																																					
A	Standard articles ②<table><tr><th>Article number</th><th>Length [mm]</th><th>Width [mm]</th><th>Thickness [mm]</th></tr><tr><td>VFSFAR-100100005-00</td><td>100</td><td>100</td><td>0.5</td></tr><tr><td>VFSFAR-100100010-00</td><td>100</td><td>100</td><td>1.0</td></tr><tr><td>VFSFAR-100100015-00</td><td>100</td><td>100</td><td>1.5</td></tr><tr><td>VFSFAR-100100020-00</td><td>100</td><td>100</td><td>2.0</td></tr><tr><td>VFSFAR-100100030-00</td><td>100</td><td>100</td><td>3.0</td></tr><tr><td>VFSFAR-100100040-00</td><td>100</td><td>100</td><td>4.0</td></tr><tr><td>VFSFAR-150150005-00</td><td>150</td><td>150</td><td>0.5</td></tr><tr><td>VFSFAR-150150010-00</td><td>150</td><td>150</td><td>1.0</td></tr><tr><td>VFSFAR-150150015-00</td><td>150</td><td>150</td><td>1.5</td></tr><tr><td>VFSFAR-150150020-00</td><td>150</td><td>150</td><td>2.0</td></tr><tr><td>VFSFAR-150150030-00</td><td>150</td><td>150</td><td>3.0</td></tr><tr><td>VFSFAR-150150040-00</td><td>150</td><td>150</td><td>4.0</td></tr></table>							Article number	Length [mm]	Width [mm]	Thickness [mm]	VFSFAR-100100005-00	100	100	0.5	VFSFAR-100100010-00	100	100	1.0	VFSFAR-100100015-00	100	100	1.5	VFSFAR-100100020-00	100	100	2.0	VFSFAR-100100030-00	100	100	3.0	VFSFAR-100100040-00	100	100	4.0	VFSFAR-150150005-00	150	150	0.5	VFSFAR-150150010-00	150	150	1.0	VFSFAR-150150015-00	150	150	1.5	VFSFAR-150150020-00	150	150	2.0	VFSFAR-150150030-00	150	150	3.0	VFSFAR-150150040-00	150	150	4.0	A
Article number								Length [mm]	Width [mm]	Thickness [mm]																																																		
VFSFAR-100100005-00								100	100	0.5																																																		
VFSFAR-100100010-00								100	100	1.0																																																		
VFSFAR-100100015-00								100	100	1.5																																																		
VFSFAR-100100020-00								100	100	2.0																																																		
VFSFAR-100100030-00								100	100	3.0																																																		
VFSFAR-100100040-00								100	100	4.0																																																		
VFSFAR-150150005-00								150	150	0.5																																																		
VFSFAR-150150010-00								150	150	1.0																																																		
VFSFAR-150150015-00								150	150	1.5																																																		
VFSFAR-150150020-00								150	150	2.0																																																		
VFSFAR-150150030-00	150	150	3.0																																																									
VFSFAR-150150040-00	150	150	4.0																																																									
B	B																																																											
C	C																																																											
D	D																																																											
E	E																																																											
F	F																																																											
G	RoHS compliant Unit:mm	Scale	Free					Date	Name	Description: Thermal foil, containing silicone, Gray white		G																																																
TOLERANCE						Drawn	08.08.2022	Segal																																																				
0~30		±0.3					Approved	08.05.2024	Segal																																																			
31~50		±0.5								ASSMANN WSW-No. VFSFAX-xxxxyyyzzz-xy																																																		
51~400		±2.0	②	Add the standard P/N in page 2 to 4	08.05.2024	Segal																																																						
DIM		TOL	①	Update	03.11.2022	Larsen	ASSMANN WSW components A company of BCS			Drawing-No. ASS 4997 HS			rev02																																															
0~1		±0.1																																																										
1~10		±10%	③	Drawn	08.08.2022	Segal				Customer-No.			SHEET 4 / 4																																															
H		T	TOL	Id.	Modification	Date	Name					H																																																
	1	2	3	4	5	6	7																																																					